



# ACROSIL A

## BUILDING PRODUCTS

Technical Data Sheet

Revised: 04/2021

### DESCRIPTION

Acetic silicon to seal bathrooms, showers, sinks, etc. Suitable for wet areas. It protects the seals from mildew.

- + Excellent adhesion on all non-porous surfaces (glass, aluminum, ceramics).
- + Great to maintain a high standard of hygiene in wet areas
- + It prevents mildew in the sealed joints
- + Not paintable
- + White and transparent

Suitable for:

- sealing leaks in showers, saunas and bathrooms.
- special for marine industry to seal galleys and refrigerator rooms.
- sealing windows in high humidity areas.
- sealing metal sheet elements in kitchens.
- particularly suitable for seals in hygienic environment or health (clinics, hospitals).
- suitable in DIY market.

### SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust, paints or oils.

### HOW TO USE IT

Cut the seal of the cartridge and use a special gun for cartridges.

### APPLICATION

Apply the elements so that ACROSIL A touch all the points of surface .

### CONSUMPTION

About 14 linear meters per cartridge.

### CLEANING

It is advisable to remove with spatula when is wet and mechanically when is dry.

### CONTRAINDICATIONS

- + Do not use at temperatures below + 5 °C
- + Application is recommended between 10 °C and + 40 °C

### PACKAGES

Cartridge 280 ml - white

code 30151

Cartridge 280 ml - transparent

code 30151T

### STORAGE

The product is guaranteed for 24 months from the date of production.

### TECHNICAL DATA

base:	acetic
appearance:	white or transparent
percentage of solid:	80%
customs code:	3214 1010
application temperature:	+ 10 °C + 40 °C
waiting time:	none
open time:	20 minutes
setting time:	24 hours

### FINAL REGULATIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI

PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com