



# ACROSIL N

## BUILDING PRODUCTS

Technical Data Sheet

Revised: 04/2021

### **DESCRIPTION**

Multi-purpose acetic silicon for sealing surface such as tile, glass, painted iron, aluminum, wood and concrete.

- + Excellent adhesion on all non-porous surfaces (glass, aluminum, ceramics)
- + not paintable
- + white and transparent

Suitable for:

- sealing leaks in showers, saunas and bathrooms.
- sealing every type of windows.
- sealing glass and doors.
- suitable in DIY market.

### **SURFACE PREPARATION**

All surfaces must be dry, absorbent, strong, free of dust, paints or oils.

### **HOW TO USE IT**

Cut the seal of the cartridge and use a special gun for cartridges.

### **APPLICATION**

Apply the elements so that ACROSIL N touch all the points of surface .

### **CONSUMPTION**

About 14 linear meters per cartridge.

### **CLEANING**

It is advisable to remove with spatula when is wet and mechanically when is dry.

### **CONTRAINDICATIONS**

- + Do not use at temperatures below + 5 °C
- + Application is recommended between 10 °C and + 40 °C

### **PACKAGES**

Cartridge 280 ml

code 30152

### **STORAGE**

The product is guaranteed for 24 months from the date of production.

### **TECHNICAL DATA**

base:	acrylic
appearance:	extra white or transparent
percentage of solid:	80%
customs code:	3214 1010
application temperature:	+ 10 °C to + 40 °C
waiting time:	none
open time:	20 minutes
setting time:	24/36 hours

### **FINAL REGULATIONS**

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI  
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com