



# ADHESIVA P

## FLOOR PRODUCTS

Technical Data Sheet

Revised: 04/2021

### DESCRIPTION

Multi purpose floor acrylic adhesive, ideal product for bonding all types of PVC coverings, linoleum, standard needle punched floorings, carpets and textile floors.

- + Fast setting
- + Strong initial tack
- + Low V.O.C. (Volatile Organic Compounds)
- + Antibacterial and anti-mold properties

Suitable for:

- coatings and PVC floorings
- linoleum
- homogeneous PVC coatings
- fiber bonded carpets and PU supports for walls
- natural cork coverings or PVC BACKED floor coverings
- thermal and absorbent floor coatings
- any type of carpet flooring backs

### SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks must be sealed with our 2-component epoxy adhesive Epoxy. The support must have a humidity: for cement surfaces max. 3% - for the areas in anhydrite. 0.5%.

On rough roads, it recommends the use of self-leveling cement-based. To make the product effective even at low temperatures use our VISOLYN ST100 as a percentage of 10% on the amount of smoothing.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet floors with fungi and mold) in case of rising damp or too humid areas.

### COATING PREPARATION

Before proceeding with the laying of the covering it is recommended to take it at the construction site the day before in order to allow an adaptation to the environment temperature.

Lay the covering by following the instructions given by the manufacturer. Unroll or simply unpack the flooring to be laid in order to decrease tensions and folds.

### PRODUCT PREPARATION

ADHESIVA P is a ready to use product.

### APPLICATION

Apply the adhesive in a single coat with a roller or a notched trowel No. 2.

ROLLER - Apply the product directly on the surface with a roll short wool for about 10/15 m<sup>2</sup>. Proceed accordingly to the application of wall covering or flooring.

SPATULA - Apply undiluted with a notched trowel No. 2 directly on the substrate to be coated. Then proceed to the preparation of materials.

### CONSUMPTION

250 - 350 g/m<sup>2</sup>

### CLEANING

We recommend to clean the joints and excess adhesive with a wet sponge. Any adhesive spillage must be removed immediately. The product does not stain.

### CONTRAINDICATIONS

- + Do not use for outdoor applications (using Adhesiva 2P/G).
- + Do not use at temperatures below + 3 ° C
- + Do not use on damp or subject to rising damp
- + Treat non-absorbent surfaces to make them porous.

### PACKAGES

bucket 700 g (12 pcs x 700 g)	code 20042
bucket 700 g (24 pcs x 700 g)	code 20043
bucket 6 kg	code 20044
bucket 13 kg	code 20045
bucket 20 kg	code 20046

### STORAGE

The product is guaranteed for 24 months from the date of production. Preserve from frost. (+ 5 ° C + 40 ° C)

### TECHNICAL DATA PRODUCT

base:	acrylic
appearance:	cream beige
Ph:	7.5
viscosity:	25,000 to 35,000 cps
percentage of solid:	70%
customs code:	3506 9100
application temperature:	+ 5 ° C + 40 ° C
waiting time:	10 - 15 minutes
open time:	20-30 minutes
setting time:	24 hours
non flammable	

### FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI  
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com