



ADHESIVA TYPE A

WALL COVERING

Technical Data Sheet

Revised: 04/2021

DESCRIPTION

Starch and methyl-cellulose based powder adhesive for any kind of wall coating.

ADHESIVA TYPE A can be used in combination with all starch based ACM adhesives.

- + Does not stain
- + Strong initial tack
- + High yield
- + Zero V.O.C. content
- + Contains antibacterial and anti-mold additives
- + Ready to use in only 5 minutes after dilution

Suitable for :

- All kinds of wallpapers and wall coverings
- Vinyl and heavy vinyl wall coverings with any kind of backing
- Foam wall coverings with any kind of backing

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks or holes in the wall must be covered with our extra-light GLASTER and in case of imperfections shaved with a normal stucco plaster.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet walls with fungi and mold) in case of rising damp or too humid.

PREPARATION AND YIELD OF THE ADHESIVE

ADHESIVA TYPE A has to be diluted in clean water following the below dilution table:

DILUTION TABLE FOR 500 GR			m ²
Normal Wallpaper	30 l	35	200
Heavy Wallpaper	25 l	30	160
Heavier Wallpaper	20 l	25	120

1. Vigorously mix the water.
2. Dilute the contents of the bag in cold water, stirring continuously.
3. Wait 3 minutes.
4. Mix again.
5. The product is ready for use after 5 minutes.



APPLICATION

Apply the product on the backing of the wall coating with a brush, or directly on the wall with a short wool roll.

BRUSH - Apply uniformly the ADHESIVA TYPE A on the back of the wall covering. Fold the sheet back on itself and wait 10 - 20 minutes depending from the temperature. Then proceed with the application of the sheet.

Video tutorial : <https://www.youtube.com/watch?v=j7zO9ekpbRg>

ROLLER - Apply the ADHESIVA TYPE A directly on the wall with a short wool roll for about 10/15 m². Proceed accordingly with the application of the wall covering.

Video tutorial: <https://www.youtube.com/watch?v=2p-pteh2B1Y>

CLEANING

We recommend to clean the wall coverings from excess adhesive and the joints with a wet sponge. Possible spillages of the adhesive should be removed immediately. We also recommend to consult the cleaning instructions of the wall covering's manufacturer before installation. THE PRODUCT DOES NOT STAIN.

CONTRAINDICATIONS

ADHESIVA TYPE A is not suitable on non-absorbent surfaces, imperfect prepared substrates, or humid walls with mold presence.

PACKAGES

Box of 1 kg
(12 x 1Kg)

cod. 10136

STORAGE

ADHESIVA TYPE A is guaranteed for 60 months from the date of production. PRODUCT NOT SENSITIVE TO FROST. Store in a dry place.

TECHNICAL DATA

base:	starch and methyl-cellulose
physical appearance:	flakes
color:	white
solid content %:	100%
customs code:	3505 2030
application temperature:	+ 5 °C + 40 °C
waiting time:	10 - 20 minutes
open time:	20 - 30 minutes
definitive adhesion:	48 hours
non flammable	
non toxic	
not sensitive to frost	

FINAL REGULATIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI

PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com