



ADHESIVA UNIFIX

BUILDING PRODUCTS

Technical Data Sheet

Revised: 04/2021

DESCRIPTION

Acrylic water-based mastic adhesive, ideal product for bonding structural elements in the building industry, thermo-acoustic insulation materials, etc.

Strong suction cup effect, strong initial adherence.

- + No highly flammable solvents
- + Free labelling EC
- + Low shrinkage
- + No nails required

Suitable for:

- structural bonding in construction
- wood/ PVC/ ceramic skirting boards
- application of tiles and ceramic mural
- polystyrene and polyurethane panels, frames and rosettes
- cork and thermo-acoustic materials
- applications in DIY

PREPARING THE SURFACE

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks must be sealed with our 2-component epoxy adhesive Epoxy.

PREPARATION

Before proceeding with the laying of the covering it is recommended to take it at the construction site the day before in order to allow an adaptation to the environment temperature.

Lay the covering by following the instructions given by the manufacturer. Unroll or simply unpack the flooring to be laid in order to decrease tensions and folds.

PREPARATION OF ADHESIVE

The adhesive is ready for use.

APPLICATION

Apply ADHESIVA UNIFIX all over the contact surface

CONSUMPTION

About 20 linear meters per cartridge.
100-300 g/m² when applied by trowels

CLEANING

Clean the equipment with fresh water, immediately after use.

CONTRAINDICATIONS

- + Do not use at temperatures below than + 3 °C
- + Application is recommended between + 10 °C to + 35 °C

PACKAGES

310 ml cartridge (24 pcs x 310 ml)	code 30076
700 g jar (12 pcs x 700 g)	code 30077
700 g jar (24 pcs x 700 g)	code 30078
Bucket 6 kg	code 30079
Bucket 13 kg	code 30080
Bucket 20 kg	code 30081

STORAGE

The product is guaranteed for 24 months from the production date

TECHNICAL DATA

base:	acrylic
appearance:	extra white color (or colored if requested)
percentage of solid:	80%
customs code:	3506 9100
application temperature:	+ 10°C + 35°C
waiting time:	none
open time:	30 - 40 minutes
setting time:	48/72 hours

FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com