



# PRIMER SP

## WALL COVERING

Technical Data Sheet

Revised: 04/2021

### **DESCRIPTION**

Acrylic water based primer for walls and floors specific for wet walls with fungi and mold.

- + Exceptional efficiency
- + High yield
- + Low V.O.C. (Volatile Organic Compounds)
- + Contains antibacterial and anti-mold (5%)

Suitable for:

- restoring old walls.
- protect and prevent molds on wet walls.
- PRIMER SP as a wall preparation before apply wall coverings and paints.

### **PRODUCT PREPARATION**

It is recommended to be diluted in water at a ratio of 1:1 (1 litre PRIMER SP in 1 litres of water). On water base paints, we recommend a dilution in 2 litres of water.

### **APPLICATION**

Once diluted, proceed to spread PRIMER SP on walls or floors with roller or brush.

The product completely dry in 2/3 hours.

<https://www.youtube.com/watch?v=LZj3MaDnuMc>

### **CONSUMPTION**

About 100 g/m<sup>2</sup> diluted.

### **CLEANING**

We recommend to clean all work tools with water, immediately after the application.

### **CONTRAINDICATIONS**

PRIMER SP is not suitable on non-absorbent surfaces (ceramic, glass, etc.)

### **PACKAGES**

plastic bottle 1 l (boxes of 10 pcs)	code 30172
Plastic tank 5 l (box of 4 pcs)	code 30173
Plastic tank 10 l	code 30174

### **STORAGE**

PRIMER SP is guaranteed for 24 months from the date of production. Preserve from frost. (+ 5 °C + 40 °C)

### **TECHNICAL DATA**

base:	acrylic water base
appearance:	liquid
color:	white
pH:	6.5
viscosity:	500/700 cps
solid:	50%
customs code:	3209 1000
application temperature:	+ 5 °C + 40 °C
drying time:	2/4 hours
non flammable	

### **FINAL REGULATIONS**

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI  
PHONE +39 02 903 611 48 | [laboratorio@acm-italy.com](mailto:laboratorio@acm-italy.com) | [www.acm-italy.com](http://www.acm-italy.com)