



PRIMER TA

WALL COVERING

Technical Data Sheet

Revised: 04/2021

DESCRIPTION

Acrylic water based primer with glass micro bubbles.
PRIMER TA create a thermal action on wall to permit to preserve more warm or fresh, in the indoor spaces depend from the season.

- + Exceptional efficiency
- + Thermic action on dump walls
- + Low V.O.C. (Volatile Organic Compounds)
- + Contains antibacterial and anti-mold

Suitable for:

- restore humid wall with mold.
- restore and renew old walls with white coating.
- removes and prevents molds on walls.

PRODUCT PREPARATION

Ready to use

APPLICATION

Proceed to spread Primer TA on walls or floors with roller or brush.
The product dries in 2/3 hours at 20/23 °C

CONSUMPTION

About 100 g/m².

CLEANING

We recommend to clean all work tools with water, immediately after the application.

CONTRAINDICATIONS

PRIMER TA is not suitable on non-absorbent surfaces (ceramic, glass, etc.)

PACKAGES

plastic bottle 1 l	code 30175
(boxes of 10 pcs)	
Plastic tank 5 l (box of 4 pcs)	code 30176
Plastic tank 10 l	code 30177

STORAGE

PRIMER TA is guaranteed for 24 months from the date of production.
Preserve from frost. (+ 5 °C + 40 °C)

TECHNICAL DATA

base:	acrylic water base
appearance:	liquid
color:	white
pH:	7.5
viscosity:	2500 ± 500 cps
solid:	55%
customs code:	3209 1000
application temperature:	+ 5 °C + 40 °C
drying time:	2/4 hours
non flammable	
protect from frost	

FINAL REGULATIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com