



RIVESTIMENTI MURALI

HIGH QUALITY POWDER ADHESIVE

WALL COVERING

Technical Data Sheet

Revised: 04/2021

DESCRIPTION

Starch based powder adhesive for any kind of wall coverings. RIVESTIMENTI MURALI can be used in combination with all starch based ACM adhesives.

- + Does not stain
- + Strong initial tack
- + High yield
- + Zero V.O.C. content
- + Contains antibacterial and anti-mold additives
- + Ready to use in only 5 minutes after dilution

Suitable for:

- all kinds of wall coverings
- vinyl and heavy vinyl with paper or non-woven backing wall coverings
- duplex wallpaper
- non-woven wall coverings

SURFACE PREPARATION


All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks or holes in the wall must be covered with our extra-light GLASTER and in case of imperfections shaved with a normal stucco plaster.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet walls with fungi and mold) in case of rising damp or too humid.

PREPARATION AND YIELD OF THE ADHESIVE

RIVESTIMENTI MURALI has to be diluted in clean water following the below dilution table:

| DILUTION TABLE FOR 250 G |  |  |
|----------------------------|---|---|
| Pre-gluing | 8/10 l | - |
| Medium weight | 6/7 l | 7 |
| Heavy weight | 5/6 l | 6 |
| Washable support and woven | 4/5 l | 4/5 |

1. Vigorously mix the water
2. Dilute the contents of the bag in cold water, stirring continuously
3. Wait 3 minutes
4. Mix again
5. The product is ready for use after 5 minutes



APPLICATION

Apply uniformly the adhesive on the back of the wall covering. Fold the sheet back on itself and wait 10 - 20 minutes depending from the temperature. Then proceed with the application of the sheet.

Video tutorial : <https://www.youtube.com/watch?v=j7zO9ekpbRg>

CLEANING

We recommend to clean the wall coverings from excess adhesive and the joints with a wet sponge.

Possible spillages of the adhesive should be removed immediately.

We also recommend to consult the cleaning instructions of the wall covering's manufacturer before installation.

THE PRODUCT DOES NOT STAIN.

CONTRAINDICATIONS

RIVESTIMENTI MURALI is not suitable on non-absorbent surfaces, imperfect prepared substrates, or humid walls with mold presence.

PACKAGES

| | |
|--|--------------------|
| Aluminum sachet of 100 g (100 pcs pack) | cod. 10015-100-100 |
| Aluminum sachet of 250 g (50 pcs pack) | cod. 10015-50-250 |
| B (100pcs pack) ox of 1 kg (12 pcs pack) | cod. 110015-12-1 |
| Box of 200 g | cod. 10015-200 |

STORAGE

RIVESTIMENTI MURALI is guaranteed for 60 months from the date of production.

PRODUCT NOT SENSITIVE TO FROST.

Store in a dry place.

TECHNICAL DATA

| | |
|--------------------------|-----------------|
| base: | starch |
| appearance: | flakes |
| color: | white |
| solid content %: | 100% |
| customs code: | 3505 2030 |
| application temperature: | + 5 °C + 40 °C |
| waiting time: | 10 - 20 minutes |
| open time: | 20 - 30 minutes |
| definitive adhesion: | 48 hours |
| non toxic | |
| not sensitive to frost | |

FINAL REGULATIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI

PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com