



SEACRIL N

BUILDING PRODUCTS

Technical Data Sheet

Revised: 04/2021

DESCRIPTION

Paintable and extra white water-based acrylic sealant.
Suction cup effect, strong initial tack.

- + No highly flammable solvents
- + Free labeling EC
- + Low shrinkage

Suitable for:

- sealing cracks on walls, plasterboards and tiles.
- sealing joints between plasterboard and metal supports
- polystyrene and polyurethane Panels frames and rosettes
- cork and thermo-acoustic materials
- applications in DIY
- no nails support required
- strong suction cup effect
- elastic and paintable

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils.
Any cracks must be sealed with our 2-component epoxy adhesive Epoxy.

PREPARATION

Before proceeding with the laying of the covering it is recommended to take it at the construction site the day before in order to allow an adaptation to the environment temperature.

Lay the covering by following the instructions given by the manufacturer.
Unroll or simply unpack the flooring to be laid in order to decrease tensions and folds.

ADHESIVE PREPARATION

The adhesive is ready for use. Cut the seal of the cartridge and use a special gun for cartridges

APPLICATION

Apply the product all over the contact surface.

CONSUMPTION

About 14 m linear cartridge
100-300 g/m² when applied by trowel

CLEANING

Clean the equipment with fresh water or remove mechanically, immediately after use.

CONTRAINDICATIONS

- + Do not use at temperatures below + 3 °C
- + Application is recommended between 10 °C and + 35 °C

PACKAGES

Cartridge 280 ml (24 pcs pack)	code 30056
Bucket 6 kg	code 30093
Bucket 13 kg	code 30094
Bucket 20 kg	code 30095

STORAGE

The product is guaranteed for 24 months from the date of production.

TECHNICAL DATA

base:	acrylic
appearance:	extra white or colored on request
percentage of solid:	85%
customs code:	3506 9100
application temperature:	+ 10 °C to +35 °C
waiting time:	none
open time:	20 minutes
setting time:	24/36 hours

FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com