



VICEVERSA CONTRACT

500 GR COMP. A + 1 KG COMP. B

WALL COVERING

Technical Data Sheet

Revised: 04/2021

DESCRIPTION

Viceversa Contract system is specially studied for easy application of contract wall coverings. Viceversa Contract two component is strong and easy to carry.

- + Does not stain
- + Strong initial tack
- + High yield
- + Zero V.O.C.
- + Contains antibacterial and anti-mold additives
- + Ready to use within 5 minutes after dilution

Suitable for applying:

- wall coverings with paper back
- wallpaper: simplex & duplex
- residential vinyl wall coverings
- fiberglass wall coverings
- contract vinyl wall coverings with fabric and non woven back

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks or holes in the wall must be covered with our extra-light GLASTER and in case of imperfections shaved with a normal stucco plaster.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet walls with fungi and mold) in case of rising damp or too humid.

PREPARATION AND YIELD OF THE ADHESIVE

1. Dilute 500 g of Comp. A in 7 Lt of water
2. Stir water during dilution with a mechanic drill and leave the mixture to settle for 2 minutes
3. AFTER dilution of Comp. A in water, ADD 1 Kg Comp. B
4. Mix vigorously with a mechanic drill
5. Ready in 5 minutes



DILUTION TABLE FOR 500 G

			m ²
Heavy vinyl and non-woven wall coverings	6 l	6	30/35
Contract wall coverings	5 l	-	25

APPLICATION

Viceversa Contract is applied in a single coat with a brush, roller, spatula or pasting machine.

BRUSH - Apply the adhesive on the back of the wall covering. Fold the sheet back on itself and wait 10 - 20 minutes depending the ambient temperature. Then proceed to apply of the sheet.

Video tutorial: <https://www.youtube.com/watch?v=j7zO9ekpbRg>

ROLLER - Apply the adhesive directly on the wall with short wool roll for about 10/15 m². Proceed accordingly to the application of the wall covering.

Video tutorial: <https://www.youtube.com/watch?v=2p-pteh2B1Y>

SPATULA - Apply the adhesive with a toothed spatula no. 1 directly on the wall. For 15 m² proceed to apply the wall coverings.

Video tutorial: <https://www.youtube.com/watch?v=316ytuK36rA>

MACHINE - Apply the adhesive with pasting machine.

CLEANING

We recommend to clean any spillage of adhesive on the wall covering surface or joints with a damp sponge. We also recommend to consult the cleaning instructions of the wall covering's manufacturer prior to installation. THE PRODUCT DOES NOT STAIN.

CONTRAINDICATIONS

The glue is not suitable on non-absorbent surfaces, imperfect prepared substrates, on damp walls or walls with mold or humidity problems.

PACKAGES

COMP. A 500 g custom code: 3912 9090
COMP. B 1 kg custom code: 3505 2010
code: 30178-VV-C
(6pcs pack)

STORAGE

The product is guaranteed for 24 months from the date of production. Can be stored up to - 20 °C. Store in a dry place.

FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI

PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com