



WALL COVERING

Technical Data Sheet Revised: 04/2021

DESCRIPTION

Concentrated adhesive for decorative wall coverings suitable for all types and weights with paper, non woven or fabric backing.

- Does not stain
- Strong initial tack
- High yield +
- Zero V.O.C.
- Contains antibacterial and anti-mold additives
- Ready to use within 5 minutes after dilution

Suitable for applying:

- wallpaper: simplex & duplex
- residential vinyl wall coverings
- fiberglass wall coverings
- contract vinyl wall coverings
- specialty decorative wall coverings

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks or holes in the wall must be covered with our extra-light GLASTER and in case of imperfections shaved with a normal stucco plaster.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet walls with fungi and mold) in case of rising damp or too humid.

PREPARATION AND YIELD OF THE ADHESIVE

VICEVERSA have to be diluted in clean water according to the table:

DILUTION TABLE FOR 500 G	6		m²
Seizing Fixing of the surface	20 l	-	200
Duplex wallpaper	8 l	9	50
Wallpapers and light vinyl wall coverings	7 L	8	45
Heavy vinyl and non-woven wall coverings	6l	6/7	35/40
Contract wall coverings	5 l	-	25/30

Fill a bucket with the correct amount of clean water. Vigorously 1. shake the squeeze packaging.

- 2. Stir the water until you create a whirlpool.
- 3. Pour the complete content of the squeeze packaging in the
- 4. whirlpool, stirring continuously.
- Wait 3 minutes. Stir again. 5
- After 5 minutes, the adhesive is ready to use. 6.



APPLICATION

BRUSH - Apply the ready adhesive on the back of the wall covering. Fold the sheet back on itself (booking) and wait 10-20 minutes depending on the ambient temperatures. Install the wall covering on the desired surface/wall.

ROLLER - Apply the ready adhesive directly on the desired surface/ wall with short wool roll for about 10/15 m2. Install the wall covering on the surface/wall.

CLEANING

We recommend to clean any spillage of adhesive on the wall covering surface or joints with a damp sponge. We also recommend to consult the cleaning instructions of the wall covering's manufacturer prior to installation. THE PRODUCT DOES NOT STAIN.

CONTRAINDICATIONS

The glue is not suitable on non-absorbent surfaces, imperfect prepared substrates, on damp walls or walls with mold or humidity problems.

PACKAGES

Squeeze packaging of 500 g 12 pz pack cod. 30160-VV12 18 pz pack Box (1kg) cod. 30160-VV18 cod. 30159-VV (2 squeeze packages of 500 g) cod. 30160-VV Tank 1Kg Tank 5Kg cod. 30167-VV5

STORAGE

The product is guaranteed for 24 months from the date of production. Can be stored up to - 20 °C. Store in a dry place.

TECHNICAL DATA

color:
base:
appearance:
solid:
customs code:
application temperature:
booking time:
open time:
curing time:
non toxic
not sensitive to frost

white liquid cream 75% 3912 9090 + 5 °C + 40 °C 10 - 20 minutes 20 - 30 minutes 48 hours

FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.

