



VISCOL PLASTEX

WALL COVERING

Technical Data Sheet

Revised: 09/28/2015

DESCRIPTION AND SPECIFICATIONS

Starch paste ready-to-use adhesive for all types of wallpapers. It can also be used in combination with all ACM starch-based products.

Apply the adhesive in a single coat with a brush, roller, spatula or automatic (pasting machine).
Ideal for commercial and contract wall coverings.

- + Exceptional adhesive strength
- + Does not stain
- + High yield
- + Zero C.O.V (Volatile Organic Compounds)
- + Antibacterial and anti-mold properties

Suitable for:

- paper backed vinyl wallpapers and non-woven wallpapers
- contract wall coverings. ideal height: from 53 cm to 160 cm
- expanded wall coverings
- non-woven wall coverings
- fiberglass wall coverings

PREPARING THE SURFACE

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks or holes in the wall must be covered with our extralight GLASTER and in case of imperfections shaved with a normal stucco plaster.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER PU in case of rising damp or humid surfaces.

PREPARATION OF ADHESIVE AND CONSUMPTION

Viscol- plastex is a ready-to-use product however when necessary, dilute it with clean water up to a maximum of 5%.

APPLICATION

Apply the adhesive in a single coat with a brush, roller, spatula or automatic (pasting machine).

BRUSH - Apply the adhesive on the back of the wall covering evenly. Fold the sheet back on itself and wait 10-20 minutes depending on the ambient temperatures. Proceed following the application of the sheet.

Video tutorial: <https://www.youtube.com/watch?v=j7zO9ekpbRg>

ROLLER - Apply the product directly on the wall with roll short wool for about 10/15 m². Proceed accordingly to the application of the wall covering.

Video tutorial: <https://www.youtube.com/watch?v=2p-pteh2B1Y>

SPATULA - Apply undiluted with a notched trowel No. 1 directly on the wall. Then proceed to the drafting of the sheets.

Video tutorial: <https://www.youtube.com/watch?v=316ytuK36rA>

MACHINE - previously dilute the adhesive VISCOL or PLASTEX with 5/10% water before using the machine.

CONSUMPTION

100 - 150 g/m²

CLEANING

Clean possible spills with a damp sponge.

THE PRODUCT DOES NOT STAIN

CONTRAINDICATIONS

Do not use the glue on non-absorbent substrates, do not lay on damp walls, with mold or on surfaces not perfectly prepared. Spillage of the adhesive should be removed immediately.

PACKAGES

Polyethylene bags of 5 kg
n boxes of No. 5 pcs

code 10001 - 10002

STORAGE

The product is guaranteed for 12 months from the date of production. Preserve from frost. (+ 5 °C + 40 °C)

TECHNICAL DATA

base:	rice starch
appearance:	white cream
pH:	6
c.o.v. .:	<0.05 g/m ³
percentage of solid:	30%
application temperature:	+ 5 °C + 40 °C
waiting time:	0 - 10 minutes
open time:	20 - 30 minutes
final setting:	48 hours
non flammable	

FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



A.C.M. Sas di Danese R. & C. | Via XXV Aprile, 62 | 20010 Bareggio /MI
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com