



VK-L

FLOOR PRODUCTS

Technical Data Sheet

Revised: 04/2021

DESCRIPTION

Water-based Vinyl adhesive, ideal product for all types of prefinished and non-prefinished solid wood floorings

- + Light brown or dark color
- + Strong final grip
- + Low C.O.V (Volatile Organic Compounds)
- + antibacterial and anti-mold properties

Suitable for:

- solid wood floorings
- wood floors on absorbent substrates
- unfinished wood floorings on ceramics (after roughing)
- wooden floors on heated substrates

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks must be sealed with our 2-component epoxy adhesive Epoxy. The support must have a humidity: for cement surfaces max. 3% - for the areas in anhydrite. 0.5%.

On rough roads, it recommends the use of self-leveling cement-based. To make the product effective even at low temperatures use our VISO-LYN ST100 as a percentage of 10% on the amount of smoothing.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet floors with fungi and mold) in case of rising damp or too humid areas.

COATING PREPARATION

Before proceeding with the laying of the covering it is recommended to take it at the construction site the day before in order to allow an adaptation to the environment temperature.

Lay the covering by following the instructions given by the manufacturer.

PRODUCT PREPARATION

VK-L is a ready to use product.

APPLICATION

Apply the adhesive in a single coat with a roller or a notched trowel No. 3.

SPATULA - Apply with a notched trowel No. 3 on the floor. Then proceed to the preparation of materials.

CONSUMPTION

800 - 1000 g/m²

CLEANING

Clean possible spills with a damp sponge. Clean The equipment with water before hardening.

CONTRAINDICATIONS

- + Do not use at temperatures below + 10 °C
- + Do not use on damp or subject to rising damp
- + Treat non-absorbent surfaces to make them porous.

PACKAGES

Bucket 6 Kg
Bucket 13 Kg
Bucket 20 Kg

code 20036
code 20037
code 20038

STORAGE

The product is guaranteed for 24 months from the date of production. Preserve from frost. (+ 5 °C + 40 °C)

TECHNICAL DATA PRODUCT

base:	vinyl
appearance:	cream light brown/dark
pH:	4.5
viscosity:	100,000 to 150,000 cps
percentage of solid:	70%
customs code:	3909 5090
application temperature:	+ 5 °C + 40 °C
waiting time:	0 - 20 minutes
open time:	30 - 40 minutes
setting time:	48/72 hours
time to wait before sanding:	20/30 days

FINAL PROVISIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com