



# VK-MT4

## FLOOR PRODUCTS

### Technical Data Sheet

Revised: 04/2021

#### DESCRIPTION

Water-based dispersion adhesive for carpet tiles, vinyl, broadloom carpets with PU foam backings and needled punched floorings.

- + Excellent open time
- + Initial grab
- + REMOVABLE with cold water
- + Low C.O.V (Volatile Organic Compounds)
- + antibacterial and anti-mold properties

Suitable for:

- Carpet in sheets or tiles
- PVC sheets or tiles
- Fiber-bonded carpet and floor-supported PU

#### SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks must be sealed with our 2-component epoxy adhesive Epoxy. The support must have a humidity: for cement surfaces max. 3% - for the areas in anhydrite. 0.5%.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet floors with fungi and mold) in case of rising damp or too humid areas.

#### COATING PREPARATION

Before proceeding with the laying of the covering it is recommended to take it at the construction site the day before in order to allow an adaptation to the environment temperature.

Lay the covering by following the instructions given by the manufacturer.

#### PRODUCT PREPARATION

VK-MT4 is a ready to use product.

#### APPLICATION

Apply the adhesive in a single coat with a short wool roller.

ROLLER - Apply the product directly on the wall with roll short wool for about 10/15 m<sup>2</sup>. Proceed accordingly to the application of the coating on the floor.

#### CONSUMPTION

150 - 250 g/m<sup>2</sup>

#### CLEANING

We recommend to clean the joints and excess adhesive with a wet sponge. Any adhesive spillage must be removed immediately. The product does not stain.

#### CONTRAINdicATIONS

- + Do not use for outdoor applications (using Adhesiva 2P/G).
- + Do not use at temperatures below + 3 °C
- + Do not use on damp or subject to rising damp
- + Treat non-absorbent surfaces to make them porous.

#### PACKAGES

bucket 6 Kg	code 20153	
bucket 13 Kg		code 20154
bucket 20 Kg		code 20155

#### STORAGE

The product guaranteed for 24 months from the date of production. Protect from frost. (+ 5 °C + 40 °C)

#### TECHNICAL DATA

base:	water
appearance:	liquid beige
pH:	8.5
viscosity:	25,000 to 35,000 cps
percentage of solid:	70%
customs code:	3506 9100
application temperature:	+ 5 °C + 40 °C
waiting time:	30 minutes - 5 hours
open time:	45-60 minutes
complete drying:	24 hours
not flammable	

#### FINAL REGULATIONS

Keep out of the reach of children and pets. Discharge the waste in special containers for building materials.



ACM Italy S.r.l. | Via Enrico Mattei, 8 | 20010 Casorezzo /MI  
PHONE +39 02 903 611 48 | laboratorio@acm-italy.com | www.acm-italy.com