

TEXRECO CONTRACT SUPER STRONG



SUPER STRONG ADHESIVE FOR
ALL TYPES OF VINYL
WALLCOVERINGS, FOR HOTELS
AND OFFICES.

TECHNICAL DATA SHEET UPDATED 20/01/2026

Product Information

Ready-to-use, super-strong paste adhesive suitable for all types of vinyl wallcoverings, specifically designed for hotels and offices.

- + Exceptional adhesive strength
- + Does not stain
- + High yield
- + Low VOC (Volatile Organic Compounds)



- Contract vinyl wallcoverings with fabric or nonwoven backing
- Fiberglass wallcoverings
- Vinyl wallcoverings with heights from 100 to 160 cm
- Heavy and rigid wallcoverings

Coverage

150 - 250 g/m²

Application Instructions

Substrate Preparation

All substrates must be dry, absorbent, sound, and free from dust, paint, or oils. Any cracks or holes should be repaired with our lightweight filler GLASTER and, if needed, leveled with standard gypsum filler. We recommend using PRIMER AC for consolidation and cleaning, and PRIMER SP for damp walls, as it is specifically formulated to combat mold and bacteria.

Product preparation

The product is ready to use; if needed, dilute with up to 5–10% clean water.

Product application

Apply the adhesive directly to the back of the wallpaper or onto the wall, following the manufacturer's instructions.

Cleaning

Remove any excess adhesive from joints with a damp sponge. THE PRODUCT DOES NOT STAIN.

Packaging

| PRODUCT CODE | WEIGHT | UNIT | PACKAGING | PCS/BOX |
|--------------|--------|------|--------------------|---------|
| 10004-C-SS-N | 5 | kg | Rectangular Bucket | 2 |

TEXRECO CONTRACT SUPER STRONG



SUPER STRONG ADHESIVE FOR
ALL TYPES OF VINYL
WALLCOVERINGS, FOR HOTELS
AND OFFICES.

TECHNICAL DATA SHEET UPDATED 20/01/2026

| | | | | |
|--------------|----|----|--------------------|---|
| 10005-C-SS-N | 10 | kg | Rectangular Bucket | - |
| 10006-C-SS-N | 15 | kg | Rectangular Bucket | - |

| | | |
|-------------------------|--------------------------|-------------|
| Technical Data | Physical appearance | White cream |
| pH | 6.5 | |
| Viscosity | 55,000–65,000 cps | |
| VOC | <0.005 mg/m ³ | |
| Solids content | Approx. 45% | |
| Customs code | 3505 2010 | |
| Application temperature | +5 °C to +40 °C | |
| Waiting time | 0–10 minutes | |
| Open time | 20–30 minutes | |
| Complete drying | 48 hours | |
| Flammability | Non-flammable | |

| | |
|-------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Warnings | Not suitable for defective substrates or damp walls. In case of damp walls, prepare the surface with PRIMER SP. |
| Storage | The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. It is essential to store the product in a dry place, away from heat sources and direct sunlight. |
| Final note | Keep out of the reach of children and pets. Dispose of waste in designated containers for construction materials. |

TEXRECO CONTRACT SUPER STRONG



SUPER STRONG ADHESIVE FOR
ALL TYPES OF VINYL
WALLCOVERINGS, FOR HOTELS
AND OFFICES.



TECHNICAL DATA SHEET UPDATED 20/01/2026

Disclaimer

The information in this technical sheet is based on our long-standing experience but is provided as a guideline.

The user is responsible for determining whether the product is suitable for their specific application and for its use.
