



TEXRECON

PASTE ADHESIVE
FOR ALL TYPES OF
WALLCOVERINGS.



TECHNICAL DATA SHEET UPDATED 18/02/2026

Product Information

A ready-to-use paste adhesive made from natural resins, designed for applying various wallcoverings. Suitable for heavy wallcoverings in offices and hotels. Can be used with all ACM powder adhesives.

- + Exceptional adhesive strength
- + Does not stain
- + High yield
- + Zero VOC (Volatile Organic Compounds)



- Vinyl wallcoverings with paper or nonwoven backing
- Vinyl wallcoverings with fabric backing – suitable for heights from 53 cm up to 160 cm
- Expanded fabric wallcoverings
- Nonwoven wallcoverings
- Fiberglass wallcoverings
- Textile wallcoverings

Coverage

150 - 250 g/m², depending on the porosity of the substrate

Application Instructions

Substrate Preparation

All substrates must be dry, absorbent, resistant and free from dust, paint and oils. Any cracks or holes must be repaired with our lightweight filler GLASTER and, in case of imperfections, leveled with standard gypsum filler. We always recommend the use of our PRIMER AC for consolidation and cleaning, and PRIMER SP, specially formulated against mold and bacteria, in case of damp walls.

Product preparation

The product is ready to use; if necessary, it can be diluted with up to 5–10% clean water.

Product application

Apply the adhesive directly to the back of the wallpaper or onto the wall surface, following the manufacturer's instructions.

Cleaning

Remove any excess product from joints with a damp sponge. **THE PRODUCT DOES NOT STAIN.**



TEXRECO N

PASTE ADHESIVE
FOR ALL TYPES OF
WALLCOVERINGS.



TECHNICAL DATA SHEET UPDATED 18/02/2026

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	10004-N-24-700	700	g	Jar	24
	10004N-6-2,5-AC-N	2,5	kg	Bucket	6
	10004-N-2-N	5	kg	Bucket	2
	10005-N-N	10	kg	Bucket	1
	10006-N-N	15	kg	Bucket	1

Technical Data	Base	Natural resins
	Physical appearance	White cream
	pH	6.5
	Viscosity	60,000–80,000 cps
	VOC	<0.005 mg/m ³
	Solids content	Approx. 35%
	Customs code	3505 2010
	Application temperature	+5 °C to +40 °C
	Waiting time	0–10 minutes
	Open time	20–30 minutes
	Complete drying	48 hours

Warnings	Do not apply on non-absorbent substrates, damp or moldy walls, or poorly prepared surfaces. Any adhesive residue should be immediately wiped away with a damp sponge.
Storage	The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date.



TEXRECO N

PASTE ADHESIVE
FOR ALL TYPES OF
WALLCOVERINGS.



TECHNICAL DATA SHEET UPDATED 18/02/2026

It is essential to store the product in a dry place, away from heat sources and direct sunlight.

Final note

Keep out of the reach of children and pets.

Dispose of waste in designated containers for construction materials.

Disclaimer

The information in this technical sheet is based on our long-standing experience but is provided as a guideline.

The user is responsible for determining whether the product is suitable for their specific application and for its use.
