

TECHNICAL DATA SHEET

REVISED: 03/03/2023

TEXRECO S PRO

READY MIXED ADHESIVES FOR WALL COVERINGS



Natural resin-based paste ready-to-use adhesive for all types of wallpaper. It can be used in combination with all ACM starch-based products. Ideal for commercial and contract wall coverings.

SUITABLE FOR

- Wall coverings with big dimensions
- Paper backed vinyl wallpapers
- Fabric based wall coverings. Height: from 100 cm to 160 cm
- Non-woven wall coverings on laminate
- Fiberglass wall coverings on plastic and ceramic tiles

Technical features

- + Good adhesive strength
- + Suitable for non-absorbent substrates (consult ACM technical office)
- + Does not stain
- + Very Low V.O.C. (Volatile Organic Compounds)

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks or holes in the wall must be covered with our extra-light stucco GLASTER and in case of imperfections shaved with a normal stucco plaster. We always recommend the use of our PRIMER AC fixative for consolidation and cleaning. We recommend using our PRIMER SP (specific for wet walls with fungi and mold) in case of rising damp or too humid surface.

PRODUCT PREPARATION

TEXRECO S PRO is a ready-to-use product however when necessary, dilute it with clean water up to a maximum of 5/10%.

APPLICATION

Apply the adhesive on the back of the wallpaper or on the wall according to manufacturer's instructions.

CONSUMPTION

About 200 -300 gr/m², depending on the porosity of the substrate

CLEANING

Clean possible spills with a damp sponge. THE PRODUCT DOES NOT STAIN

CONTRAINDICATIONS

TEXRECO S PRO is not suitable on non-absorbent substrates, humid walls with mold or on surfaces not perfectly prepared. Spillage of the adhesive should be removed immediately with a damp sponge.

TECHNICAL DATA SHEET

REVISED: 03/03/2023

TEXRECO S PRO

READY MIXED ADHESIVES FOR WALL COVERINGS



PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
100011	700	g	Bucket	24
100012	5	kg	Bucket	2
100013	10	kg	Bucket	1
100014	15	kg	Bucket	1

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 18 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

TECHNICAL PRODUCT DATA

Base	Natural Resin
Appearance and colour	White cream
PH	6.5
Viscosity	55000-65000 cps
VOC	< 0.005 mg/ m ³
Solids percentage	about 45%
Customs code	3505 2010
Application temperature	+5°C +40°C
Waiting Time	0-10 min
Open Time	20-30 min
Drying Time	48 hours
Non-Flammable product	
Keep free from frost	

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.

www.acm-italy.com