



# TEXRECO S PRO

READY-TO-USE PASTE  
ADHESIVE FOR THE  
APPLICATION OF ALL TYPES OF  
WALL COVERINGS



TECHNICAL DATA SHEET UPDATED 18/02/2026

## Product Information

Ready-to-use paste adhesive based on natural resins, designed for the application of all types of wall coverings.  
Suitable for commercial and contract wall coverings.  
Can also be used in combination with all ACM powder products.

- + Exceptional adhesive strength
- + Non-staining
- + Suitable for non-absorbent substrates (consult ACM Technical Department)
- + Zero VOC (Volatile Organic Compounds)



- Large-format wall coverings
- Vinyl wall coverings with paper backing
- Fabric-textured wall coverings (suitable for heights from 100 to 160 cm)
- Non-woven wall coverings on laminate
- Fiberglass wall coverings on plastic and ceramic tiles

## Coverage

200–300 g/m<sup>2</sup>

## Application Instructions

### Substrate Preparation

All substrates must be dry, absorbent, sound, and free from dust, paint, and oils. Any cracks or holes must be repaired with our lightweight filler GLASTER and, in the case of surface imperfections, leveled with a standard gypsum filler. We recommend the use of our PRIMER AC for consolidation and cleaning, and PRIMER SP, specifically formulated against mold and bacteria, in the case of damp walls.

### Product preparation

The product is ready to use. If necessary, dilute with clean water up to a maximum of 5–10%.

### Product application

Apply the adhesive directly to the back of the wallpaper or onto the wall, according to the wallpaper manufacturer's instructions.

## Cleaning



# TEXRECO S PRO



READY-TO-USE PASTE  
ADHESIVE FOR THE  
APPLICATION OF ALL TYPES OF  
WALL COVERINGS

TECHNICAL DATA SHEET UPDATED 18/02/2026

Any adhesive residues at the joints must be removed with a damp sponge.  
THE PRODUCT DOES NOT STAIN.

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	100011	700	g	Jar	24
	100012	5	kg	Bucket	2
	100013	10	kg	Bucket	1
	100014	15	kg	Bucket	1

Technical Data	Base	Natural resins
	Physical appearance	White cream
	pH	6.5
	Viscosity	55,000–65,000 cps
	VOC	< 0.005 mg/m <sup>3</sup>
	Solids content	Approx. 45%
	Customs code	3505 2010
	Application temperature	+5°C to +40°C
	Waiting time	0–10 minutes
	Open time	20–30 minutes
	Complete drying	48 hours

Warnings	The product is not suitable for damp walls affected by mould or for substrates that are not perfectly prepared. Any adhesive spills must be removed immediately with a damp sponge.
----------	---



# TEXRECO S PRO

READY-TO-USE PASTE  
ADHESIVE FOR THE  
APPLICATION OF ALL TYPES OF  
WALL COVERINGS



TECHNICAL DATA SHEET UPDATED 18/02/2026

---

## Storage

The product is guaranteed, in its original unopened packaging and under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. Store in a dry place, away from heat sources and direct sunlight.

---

## Final note

Keep out of reach of children and pets. Dispose of waste in suitable containers for construction materials, in accordance with local regulations.

---

## Disclaimer

The information provided in this Technical Data Sheet is based on our many years of experience and is to be considered indicative only. Users must verify the suitability of the product for the intended application and assume full responsibility for its use.

---