

TECHNICAL DATA SHEET

REVISED: 06/12/2022

TEXRECO TDV

READY MIXED ADHESIVES FOR WALL COVERINGS



Natural resin-based paste ready-to-use adhesive for all types of wallpapers. Specifically, for fiberglass wall coverings. It can be used in combination with all ACM starch-based products. Also for wall coverings for contract and commercial applications.

Suitable for:

- Heavy vinyl wallpapers with paper or non-woven backing
- Heavyweight, paintable and non-paintable non-woven wall coverings
- Expanded wall coverings
- Fiberglass wall coverings, any thickness
- Thermal and sound absorbing wall coverings

TECHNICAL FEATURES

- + Exceptional adhesive strength
- + Does not stain
- + High yield
- + Very Low V.O.C. (Volatile Organic Compounds)

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks or holes in the wall must be covered with our extra-light stucco GLASTER and in case of imperfections shaved with a normal stucco plaster. We always recommend the use of our PRIMER AC fixative for consolidation and cleaning. We recommend using our PRIMER SP (specific for wet walls with fungi and mold) in case of rising damp or too humid surface.

PRODUCT PREPARATION

TEXRECO TDV is a ready-to-use product however, when necessary, dilute it with clean water up to a maximum of 5/10%.

APPLICATION

Apply the adhesive on the back of the wallpaper or on the wall according to manufacturer's instructions.

CONSUMPTION

About 150 -250 gr/m2, depending on the porosity of the substrate

CLEANING

Clean possible spills with a damp sponge. THE PRODUCT DOES NOT STAIN

CONTRAINDICATIONS

TEXRECO TDV Is not suitable on non-absorbent substrates, humid walls with mold or on surfaces not perfectly prepared. Spillage of the adhesive should be removed immediately with a damp sponge.

TECHNICAL DATA SHEET

REVISED: 06/12/2022

TEXRECO TDV

READY MIXED ADHESIVES FOR WALL COVERINGS



PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
10004-TDV-2-N	5	kg	Bucket	2
10005-TDV-N	10	kg	Bucket	1
10006-TDV-N	15	kg	Bucket	1

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 18 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

TECHNICAL PRODUCT DATA

Base	Natural Resin
Appearance and colour	White cream
PH	6.5
Viscosity	40000-50000 cps
VOC	< 0.005 mg/ m3
Solids percentage	about 25%
Customs code	3505 2010
Application temperature	+5°C +40°C
Waiting Time	0-10 min
Open Time	20-30 min
Drying Time	48 hours
Non-Flammable product	
Keep free from frost	

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.

www.acm-italy.com