



# TEXRECO TDV



PASTE ADHESIVE FOR  
FIBERGLASS WALL COVERINGS  
AND HEAVY WALL COVERINGS.

TECHNICAL DATA SHEET UPDATED 19/02/2026

## Product Information

Ready-to-use paste adhesive based on natural resins, specifically developed for the installation of fiberglass wall coverings. Compatible with all ACM powder products, it is also suitable for commercial and contract wall covering applications.

- + Good adhesive strength
- + Non-staining
- + Zero VOC (Volatile Organic Compounds)



- Heavy vinyl wallpapers with paper or non-woven backing
- Heavy non-woven wall coverings, paintable or non-paintable
- Expanded vinyl wall coverings
- Fiberglass wall coverings of any thickness
- Thermo-acoustic insulating wall covering

## Coverage

150–250 g/m<sup>2</sup>

## Application Instructions

### Substrate Preparation

All substrates must be dry, absorbent, sound, and free from dust, paint, and oils. Any cracks or holes must be repaired with our lightweight filler GLASTER and, in the case of surface imperfections, leveled with a standard gypsum filler. We recommend the use of our PRIMER AC for consolidation and cleaning, and PRIMER SP, specifically formulated against mold and bacteria, in the case of damp walls.

### Product preparation

The product is ready to use. If necessary, dilute with clean water up to a maximum of 5–10%.

### Product application

Apply the adhesive directly to the back of the wallpaper or onto the wall, according to the wallpaper manufacturer's instructions.

### Cleaning

Any adhesive residues at the joints must be removed with a damp sponge.  
THE PRODUCT DOES NOT STAIN.

PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
--------------	--------	------	-----------	---------



# TEXRECO TDV



PASTE ADHESIVE FOR  
FIBERGLASS WALL COVERINGS  
AND HEAVY WALL COVERINGS.

TECHNICAL DATA SHEET UPDATED 19/02/2026

<b>Packaging</b>	10004-TDV-2-N	5	kg	Bucket	2
	10005-TDV-N	10	kg	Bucket	2
	10006-TDV-N	15	kg	Bucket	1

<b>Technical Data</b>	Base	Natural resins
	Physical appearance	White cream
	pH	6.5
	Viscosity	40,000–50,000 cps
	VOC	< 0.005 mg/m <sup>3</sup>
	Solids content	Approx. 25%
	Customs code	3505 2010
	Application temperature	+5°C to +40°C
	Waiting time	0–10 minutes
	Open time	20–30 minutes
	Drying time	48 hours

<b>Warnings</b>	Do not use the product on non-absorbent substrates. Do not apply on damp walls affected by mould or on substrates that are not perfectly prepared. Any adhesive spills must be removed immediately with a damp sponge.
<b>Storage</b>	The product is guaranteed, in its original unopened packaging and under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. Store in a dry place, away from heat sources and direct sunlight.
<b>Final note</b>	Keep out of reach of children and pets. Dispose of waste in suitable containers for construction materials, in accordance with local regulations.
<b>Disclaimer</b>	The information provided in this Technical Data Sheet is based on our many years of experience and is to be considered indicative only. Users



# TEXRECO TDV

---



PASTE ADHESIVE FOR  
FIBERGLASS WALL COVERINGS  
AND HEAVY WALL COVERINGS.

TECHNICAL DATA SHEET UPDATED 19/02/2026

---

must verify the suitability of the product for the intended application and  
assume full responsibility for its use.

---