

# **TECHNICAL DATA SHEET**

REVISED: 10/05/2023

## **VICEVERSA**

### **PROFESSIONAL LINE FOR WALL COVERINGS**



Liquid adhesive for the installation of wallcoverings. Suitable for application with all types of wallcoverings on all substrates.

Suitable for:

- Wallpaper
- Duplex
- Vinyl wallcoverings with paper backing or non-woven substrate
- Glass fibre wallcoverings
- Expanded vinyl wallcoverings with non-woven substrate
- Paintable non-woven wallcovering

#### **TECHNICAL FEATURES:**

- + Does not stain
- + Strong initial grab
- + High Yield
- + Zero VOC (Volatile Organic Compounds)
- + Ready to use after only 5 minutes dilution

#### **SURFACE PREPARATION**

All surfaces must be clean and dry, absorbent and free from dust, paint and oil. Any cracks or holes in the wall must be filled with our light GLASTER filler and, in case of imperfections, smoothed with a normal plaster filler. We recommend using our PRIMER AC primer for preparation and cleaning, and our PRIMER SP (created for resistance to mold and bacteria) where the walls are damp.

#### **PRODUCT PREPARATION**

The product should be diluted in clean water

1. Stir the water vigorously
2. Tip the contents of the pack into the water, continuing to stir.
3. Leave to settle for 3 minutes
4. Continue to stir
5. After a further 5 minutes the product is ready to be used

#### **APPLICATION**

Apply the adhesive on the back of the wallpaper or on the wall according to manufacturer's instructions.

#### **CLEANING**

It is recommended to wipe off any excess paste from joints and edges using a damp cloth. THIS PRODUCT DOES NOT LEAVE ANY MARKS.

#### **CONTRAINDICATIONS**

Do not use this product on a non-absorbent surface, do not apply to damp or moldy walls, or where the surface has not been prepared adequately. Any excess paste on the surface must be wiped off immediately using a damp cloth.

# TECHNICAL DATA SHEET

REVISED: 10/05/2023

## VICEVERSA

### PROFESSIONAL LINE FOR WALL COVERINGS



#### PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30160-VV18	500	g	Squeeze Packaging	18
30160-VV-N	1	kg	Plastic Bottle	12
30167-VV5-N	5	kg	Tank	4

#### STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 24 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

#### TECHNICAL PRODUCT DATA

Base	Liquid
Physical Appearance	White cream
Percentage of Solids	Approx 75%
Customs Code	3912 9090
Operating Temperature	+5°C +40°C
Waiting Time	10-20 minutes
Open Time	20-30 minutes
Completely Dry	48 hours
Non inflammable	

#### FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

#### DISCLAIMER

The information contained in the data sheet, based on results of our long experience, are for information only. Therefore, those who intend to use it are required to assess whether the product is suitable for their use, and to assume responsibility for its use.