



# ADHESIVA CUBE

VACUUM-SEALED POWDER  
ADHESIVE FOR ALL TYPES OF  
WALLCOVERINGS



TECHNICAL DATA SHEET UPDATED 03/12/2025

---

## Product Information

Powder adhesive for all types of wallcoverings. Also compatible with all ACM paste products.

- + Non-staining
- + Strong initial tack
- + High yield
- + Ready to use in just 5 minutes
- + Vacuum system
- + Zero VOC (volatile organic compounds)



---

## Recommended Uses

- All types of wallcoverings
- Vinyl wallcoverings with paper or nonwoven backing
- Duplex paper
- Expanded wallcoverings with paper or nonwoven backing
- Heavy vinyl wallcoverings with paper or nonwoven backing
- Nonwoven wallcoverings

---

## Application Instructions

### Substrate Preparation

All substrates must be dry, absorbent, sound, and free from dust, paint, or oils.

Cracks or holes should be filled with our lightweight filler GLASTER and, if needed, smoothed with a standard gypsum-based filler.

We recommend using our PRIMER AC for surface consolidation and cleaning, and PRIMER SP (anti-mold and antibacterial) for damp walls.

---

### Product Dilution

Dilute the product in clean water according to the ratio shown on the package.

---

### Product Preparation

1. Stir water vigorously.
2. Pour the powder into the water while continuing to stir.
3. Let rest for 3 minutes.
4. Stir again.
5. Ready to use after 5 minutes.

---

### Product Application

Apply the adhesive directly to the back of the wallpaper or to the wall, following the wallpaper manufacturer's instructions.



# ADHESIVA CUBE

VACUUM-SEALED POWDER  
ADHESIVE FOR ALL TYPES OF  
WALLCOVERINGS



TECHNICAL DATA SHEET UPDATED 03/12/2025

## Cleaning

Clean any excess adhesive from joints with a damp sponge. THE PRODUCT DOES NOT STAIN.

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	10137-1	1.0 kg	Bag	Vacuum-sealed pack	9
	10137-2	2.0 kg	Bag	Vacuum-sealed pack	4

## Technical Data

Physical appearance	Powder
Color	White
Solids content	100%
Customs code	3505 2030
Flammability	No
Application temperature	+5 °C to +40 °C
Waiting time	10–20 minutes
Open time	20–30 minutes
Full drying time	48 hours
Non-toxic	Yes
Frost-resistant	Yes

## Warnings

- Do not use the adhesive on non-absorbent substrates.
- Do not apply on damp or moldy walls or poorly prepared surfaces.
- Remove any adhesive excess immediately with a damp sponge.

## Storage

The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 60 months from the production date.



# ADHESIVA CUBE

VACUUM-SEALED POWDER  
ADHESIVE FOR ALL TYPES OF  
WALLCOVERINGS



TECHNICAL DATA SHEET UPDATED 03/12/2025

	It is essential to store the product in a dry place, away from heat sources and direct sunlight.
<b>Final note</b>	Keep out of the reach of children and pets. Dispose of waste in designated containers for construction materials.
<b>Disclaimer</b>	The information in this technical sheet is based on our long-standing experience but is provided as a guideline.  The user is responsible for determining whether the product is suitable for their specific application and for its use.