

# TECHNICAL DATA SHEET

REVISED: 18/05/2022

## PRIMER+ PLUS

### PRIMERS AND WALL PREPARATION



Anti-mold, antibacterial and sanitizing PRIMER for walls and floors; Primer+ Plus contains our exclusive sanitizing gel based on Thymol, THYMOLGEL®. The antibacterial and antiviral thymol is a phenol derived from the Thyme plant.

Suitable for:

- Sanitize new and old walls;
- Protect and prevent the appearance of fungi and mildew;
- Harden and protect the walls surfaces;
- Preparation for the application of paints, wall coverings, vinyl flooring and LVT

Technical features:

- + Ready-to-use
- + Acrylic Resin basis
- + Does not drip
- + Very Low V.O.C.
- + Contains Thymol

#### **PRODUCT PREPARATION**

Primer+ Plus is a ready-to-use product. The product can also be diluted in water with a ratio of 1:1 (1 liter PRIMER+ PLUS in 1 litre of water).

#### **PRODUCT APPLICATION**

Proceed to spread Primer+ Plus on walls and/or floors with a roller or a brush.

The product dries completely in 3/4 hours at 20-23°C. The drying time can vary based upon the temperature and characteristics of the work environment.

#### **CONSUMPTION**

About 100-200 gr/m<sup>2</sup>, depending on the porosity of the substrate.

#### **CLEANING**

We recommend cleaning all the work tools with water, immediately after use.

#### **CONTRA-INDICATIONS**

Primer+ Plus is not suitable on non-absorbent surfaces (ceramic, glass, laminates). Protect from frost.

#### **PACKAGING**

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30196-N	1	Litre	Bottle	10
30193-N	2,5	Litres	Rectangular bucket with aluminium bag	6
30194-N	5	Litres	Rectangular Bucket	4
30195-N	10	Litres	Rectangular Bucket	1

[www.acm-italy.com](http://www.acm-italy.com)

# TECHNICAL DATA SHEET

REVISED: 18/05/2022

## **PRIMER<sup>+</sup> PLUS**

### PRIMERS AND WALL PREPARATION



#### STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 24 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

#### TECHNICAL PRODUCT DATA

<b>Base</b>	<b>Acrylic, Water Base</b>
<b>Appearance and colour</b>	Light blue liquid
<b>PH</b>	7.7
<b>Viscosity</b>	1000-1200 cps
<b>Solids percentage</b>	35%
<b>Customs code</b>	3209 1000
<b>Application temperature</b>	+5°C +40°C
<b>Drying Time</b>	3 / 4 hours
<b>Non-Flammable product</b>	
<b>Keep free from frost</b>	

#### FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials.

#### DISCLAIMER

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.