



ADHESIVA M

POWDERED ADHESIVE FOR HEAVY WALLCOVERINGS



TECHNICAL DATA SHEET UPDATED 12/02/2026

Product Information

Powdered adhesive specifically formulated for heavy wallcoverings in non-woven fabric or fiberglass. The adhesive includes a temporary pink tracer that disappears approximately 2 minutes after application.

- + Does not stain
- + Strong initial grab
- + High coverage
- + Ready to use in just 5 minutes
- + Zero VOC (volatile organic compounds)



Recommended Uses

- Non-woven wallcoverings
- Vinyl wallcoverings with non-woven backing
- Fiberglass wallcoverings
- Expanded wallcoverings with non-woven backing

Application Instructions

Substrate Preparation

All surfaces must be dry, absorbent, sound, and free from dust, paint, or oil. Any cracks or holes should be filled with our lightweight filler GLASTER, and if needed, skimmed with a standard gypsum-based filler. We recommend using our PRIMER AC for consolidation and cleaning, and PRIMER SP (special anti-mold and antibacterial) for damp walls.

Product Dilution

Dilute the product in clean water according to the ratio shown on the package.

Product Preparation

1. Stir water vigorously.
2. Pour the powder into the water while continuing to stir.
3. Let rest for 3 minutes.
4. Stir again.
5. Ready to use after 5 minutes.

Product Application

Apply the adhesive directly to the back of the wallpaper or to the wall, following the wallpaper manufacturer's instructions.

Cleaning

Clean any excess adhesive from joints with a damp sponge. THE PRODUCT DOES NOT STAIN.



ADHESIVA M

POWDERED ADHESIVE FOR
HEAVY WALLCOVERINGS



TECHNICAL DATA SHEET UPDATED 12/02/2026

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	10167-250	250	g	Carton	24
	10167-500	500	g	Carton	12

Technical Data		
Physical appearance		Powder
Color		White
Solids content		100%
Customs code		3505 2030
Flammability		No
Application temperature		+5 °C to +40 °C
Waiting time		10–20 minutes
Open time		20–30 minutes
Full drying time		48 hours
Non-toxic		Yes
Frost-resistant		Yes

Warnings

- Do not use the adhesive on non-absorbent substrates.
- Do not apply on damp or moldy walls or poorly prepared surfaces.
- Remove any adhesive excess immediately with a damp sponge.

Storage

The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 60 months from the production date.
It is essential to store the product in a dry place, away from heat sources and direct sunlight.

Final note

Keep out of the reach of children and pets.
Dispose of waste in designated containers for construction materials.



ADHESIVA M

POWDERED ADHESIVE FOR
HEAVY WALLCOVERINGS



TECHNICAL DATA SHEET UPDATED 12/02/2026

Disclaimer

The information in this technical sheet is based on our long-standing experience but is provided as a guideline.

The user is responsible for determining whether the product is suitable for their specific application and for its use.
