

## **TECHNICAL DATA SHEET**

REVISED: 01/09/2022

# **ADHESIVA MS FAST**

## **SEALANTS AND MOUNTING**



Silane-modified polymer-based construction adhesive, for bonding structural building materials.

Suitable for:

- Structural bonding construction adhesive
- All types of metal sheets, flashings and gutters
- Vertical applications
- Polystyrene and polyurethane panels and elements, indoors and outdoors
- Adhesion for non-absorbent elements (metal, glass, plastic), indoors and outdoors

### **TECHNICAL FEATURES:**

- + Strong adhesion
- + Strong suction cup effect
- + Low elasticity modulus
- + Solvent free
- + Low VOC
- + No shrinkage
- + Strong initial tack

### **SURFACE PREPARATION**

All surfaces must be dry, absorbent, strong, free of dust, paints or oils. Any cracks or holes in the wall must be covered with our extra-light filler GLASTER.

### **ADHESIVE PREPARATION**

Mono-component adhesive and ready-to-use. Cut the seal of the cartridge and use a special caulking gun for cartridges.

### **APPLICATION**

Apply the product all over the contact surface.

### **CONSUMPTION**

About 18/20 m (linear) per cartridge

### **CLEANING**

Clean the equipment with a nitro diluent

### **CONTRAINDICATIONS**

- Do not use at temperatures below +3 °C
- Application is recommended between +10 °C and +35 °C

### **PACKAGING**

<b>PRODUCT CODE</b>	<b>WEIGHT</b>	<b>UNIT</b>	<b>TYPE OF PACKAGING</b>	<b>PCS IN BOX</b>
30001	300	ml	Cartridge	24

**ACM Italy S.r.l.**

Viale Enrico Mattei, 8 - 20010 Casorezzo (Milano) - Telefono +39 02 90361148 r.a. - Fax +39 02 9013173 - e-mail: info@acm-italy.com

C.C.I.A.A. MI-1952713 - Cod. Fisc. e P. IVA 07352030964

## **TECHNICAL DATA SHEET**

REVISED: 01/09/2022

# **ADHESIVA MS FAST**

## **SEALANTS AND MOUNTING**



### **STORAGE**

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 12 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

### **PRODUCT TECHNICAL DATA**

<b>Base</b>	Silane Modified polymers
<b>Appearance and colour</b>	Extra White
<b>Solids percentage</b>	about 80%
<b>Customs code</b>	3909 5090
<b>Application temperature</b>	+10°C +35°C
<b>Waiting Time</b>	None
<b>Open Time</b>	About 30-40 min
<b>Setting Time</b>	48/72 hours

### **FINAL REGULATIONS**

Keep out of reach of children. Discharge the waste in special containers for building materials

### **DISCLAIMER**

The above mentioned information and prescriptions, even if they correspond to our best experience are purely indicative and must be confirmed by practical applications. Therefore, before using it, is necessary to establish if it fits the prescribed use and the final customer assumes any responsibility that may derive from its use.

---

**ACM Italy S.r.l.**

Viale Enrico Mattei, 8 - 20010 Casorezzo (Milano) - Telefono +39 02 90361148 r.a. - Fax +39 02 9013173 - e-mail: info@acm-italy.com

C.C.I.A.A. MI-1952713 - Cod. Fisc. e P. IVA 07352030964