



# ADHESIVA MS FAST

STRUCTURAL ADHESIVE –  
SILANE-MODIFIED POLYMER  
BASED



TECHNICAL DATA SHEET UPDATED 12/02/2026

---

## Product Information

Single-component adhesive based on silane-modified polymers, specifically designed for structural bonding in construction.

- + Strong adhesion
- + Suction effect
- + Low modulus of elasticity
- + Solvent-free
- + Low VOC (volatile organic compounds)
- + Low shrinkage
- + High initial tack

---

## Recommended Uses

- Structural bonding in construction
- Sheet metal joints, flashings, and gutters
- Vertical installations
- Polyurethane and polyester elements, including outdoor use
- Bonding of non-absorbent materials (e.g., metal, glass, plastic) in both indoor and outdoor settings

---

## Coverage

Approx. 18–20 linear meters per cartridge

---

## Application Instructions

### Substrate Preparation

All surfaces must be dry, absorbent, sound, and free from dust, paint, or oil residues.

Cracks should be filled with our ultra-light filler GLASTER

---

### Product Preparation

Ready-to-use single-component product. Cut the cartridge seal and apply using a suitable dispensing gun.

---

### Product Application

Apply the adhesive and press the elements together to ensure complete wetting of the surfaces.

---

### Cleaning

Clean any excess adhesive from joints with a damp sponge. The product does not stain.



# ADHESIVA MS FAST

STRUCTURAL ADHESIVE –  
SILANE-MODIFIED POLYMER  
BASED



TECHNICAL DATA SHEET UPDATED 12/02/2026

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX	
	30001	300	ml	Cartridge	24	
<b>Technical Data</b>						
		Base	Silane-modified polymers			
		Appearance	Extra white			
		Solids content	Approx. 80%			
		Customs code	3909 5090			
		Application temperature range	+10 °C to +35 °C			
		Waiting time	None			
		Open time	Approx. 30–40 minutes			
		Final setting time	48–72 hours			
<b>Warnings</b>		<ul style="list-style-type: none"><li>Do not apply at temperatures below +3 °C</li><li>Recommended application between +10 °C and +35 °C</li></ul>				
<b>Storage</b>		The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 12 months from the production date. It is important to store the product in a dry place, away from heat sources and direct sunlight.				
<b>Final note</b>		Keep out of reach of children and pets. Dispose of waste in designated construction material containers. The information in this technical sheet is based on our extensive experience but is indicative. Users must assess product suitability for their specific use and are responsible for its application.				