

# **TECHNICAL DATA SHEET**

REVISED: 02/12/2022

## **ADHESIVA P**

### **ADHESIVES FOR TEXTIL, PVC AND LINOLEUM FLOORINGS**



General purpose acrylic adhesive for the installation of all types of PVC coatings, linoleum, tufted wall and flooring tiles, carpets

Suitable for:

- PVC flooring and tiles
- Linoleum
- Pure PVC flooring
- Tufted wallcoverings on polyurethane backing
- Cork wallcovering with or without PVC backing
- Thermal and acoustic-absorbent wallcovering
- Linoleum
- Carpet with any type of backing

#### **TECHNICAL FEATURES:**

- + Strong grab
- + High initial grab
- + Low VOC (volatile organic compounds)
- + General purpose use

#### **PREPARATION OF SURFACE**

All grounds and surfaces must be dry, porous, dust-free and free from paint and oil. Any gaps should be sealed using our 2-part epoxy adhesive EPOXY ECO. The surface should have a maximum humidity: Cement max 3%; Gypsum max 0.5%. On uneven surfaces we recommend using a cement-based auto-levelling screed. To further improve the levelling, we also suggest using our VISOLYN ST100 in a 10% addition to the levelling screed. We always recommend the use of our PRIMER AC sealant for consolidation and cleanliness.

#### **PREPARATION OF MATERIALS**

Before commencing installation, we suggest leaving the materials on site for one day prior to commencing work in order for it to be done at room temperature. Apply the product in accordance with the manufacturer's recommended installation temperature. Carefully unpack or unroll the product to permit it to relax and reduce creasing.

#### **PRODUCT PREPARATION**

The product is ready to use

#### **PRODUCT APPLICATION**

The adhesive can be applied in one coat using either a roller or a number 2 grooved spatula.

BY ROLLER – Apply the product directly to the wall using a short-pile woollen roller to an area of approx. 10/15m<sup>2</sup>. Install the wallcovering or flooring according to the manufacturer's instructions.

BY SPATULA – Apply undiluted product using a number 2 grooved spatula directly to the surface to be covered. Then apply the material in accordance with the manufacturer's instructions.

# TECHNICAL DATA SHEET

REVISED: 02/12/2022

## ADHESIVA P

ADHESIVES FOR TEXTIL, PVC AND LINOLUEM FLOORINGS



### COVERAGE

250-350g/m<sup>2</sup>

### CLEANING

We recommend removing any excess product from the seams using a damp cloth.

### ADVICE

- Do not use for external installations (use ADHESIVA 2P/G)
- Do not use where temperature is below 3 degrees C
- Do not use on humid surfaces or where there is rising damp
- Treat non-absorbent surfaces so they become porous

### PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
20043	700	g	Small bucket	24
20044-N	6	kg	Bucket	1
20045-N	13	kg	Bucket	1
20046-N	20	kg	Bucket	1

### STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 18 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

### PRODUCT TECHNICAL DATA

Base	Acrylic
Physical appearance	Beige paste
PH	7.5
Viscosity	25000-35000 cps
Percentage of solids	Circa 70%
Customs Code	3506 9100
Application Temperature	+5°C +40°C
Wait time	10-15 minutes
Open time	20-30 minutes
Completely dry	24 hours
Non-Flammable	

[www.acm-italy.com](http://www.acm-italy.com)

## **TECHNICAL DATA SHEET**

REVISED: 02/12/2022

# **ADHESIVA P**

**ADHESIVES FOR TEXTIL, PVC AND LINOLUEM FLOORINGS**



### **SAFETY ADVICE**

Keep away from babies and infants. Dispose of waste in containers suitable for building materials.

### **GUIDANCE**

The information contained in this technical data sheet, resulting from our long experience, is purely indicative. Moreover, we advise that the user checks that the product is suitable for the purpose for which it is intended, and that they are responsible for its use.