



ADHESIVA P

UNIVERSAL ACRYLIC ADHESIVE



TECHNICAL DATA SHEET UPDATED 18/12/2025

Product Information

Universal acrylic adhesive suitable for the installation of all types of PVC coverings, linoleum, needle-punched fabrics for walls and floors, and carpets.

- + Quick setting
- + Strong initial grab
- + Low VOC (volatile organic compounds)
- + Universal use

Recommended Uses

- PVC coverings and flooring, including homogeneous types
- Linoleum in sheets or tiles
- Homogeneous PVC wallcoverings
- Needle-punched and wall-mounted carpets with polyurethane backing
- Cork wallcoverings or coverings with PVC backing
- Sound-absorbing and thermal-insulating materials for wall applications
- Carpets with any type of backing

Coverage

250–350 g/m² depending on the type of covering and substrate

Application Instructions

Substrate Preparation

All substrates must be dry, absorbent, resistant, and free from dust, paint, or oil. Any cracks should be sealed using our EPOXY ECO two-component adhesive.

For uneven surfaces, we recommend applying a powder-based leveling compound such as our SELF LEVEL FLOORING (Suprimo line) or the ready-to-use TILECOAT.

To consolidate and clean the surface, use our PRIMER SP. In case of moisture rising or very humid substrates, use PRIMER PU.

Product Preparation

Ready-to-use product.

Product Application

Apply the adhesive in a single coat using a wool roller or notched trowel No. 2, depending on the substrate and material type.



ADHESIVA P

UNIVERSAL ACRYLIC ADHESIVE



TECHNICAL DATA SHEET UPDATED 18/12/2025

Roller application: spread the undiluted product evenly using a short-pile wool roller over areas of 10–15 m² at a time. Proceed immediately with the installation.

Trowel application: apply the undiluted adhesive with a No. 2 notched trowel to ensure even distribution. Place the wallcovering or flooring material and press firmly to ensure proper adhesion.

Cleaning

Remove fresh adhesive residues immediately with a damp sponge. Once hardened, mechanical methods may be required for removal.

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	20043	700	g	Jar	24
	20044-N	6	kg	Buckets	1
	20045-N	13	kg	Buckets	1
	20046-N	20	kg	Buckets	1

Technical Data	Base	Acrylic dispersion
Appearance	Beige cream	
pH	7.5	
Viscosity	25,000 – 35,000 cps	
Solids content	Approx. 70%	
Customs code	3506 91 90	
Application temperature range	+5 °C to +40 °C (+41 °F to +104 °F)	
Waiting time	10–15 minutes	
Open time	20–30 minutes	
Full drying time	24 hours	
Flammability	Non-flammable	



ADHESIVA P

UNIVERSAL ACRYLIC ADHESIVE



TECHNICAL DATA SHEET UPDATED 18/12/2025

Warnings

- Not suitable for outdoor applications. For external use, refer to ADHESIVA 2P/G.
- Do not apply below +3 °C.
- Do not use on damp substrates or those subject to rising damp.
- For non-absorbent surfaces, mechanical or chemical preparation is required to ensure surface porosity and proper adhesion.

Storage

The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. It is important to store the product in a dry place, away from heat sources and direct sunlight.

Final note

Keep out of reach of children and pets. Dispose of waste in designated construction material containers.

The information in this technical sheet is based on our extensive experience but is indicative. Users must assess product suitability for their specific use and are responsible for its application.