

TECHNICAL DATA SHEET

REVISED: 01/09/2022

ADHESIVA SBR

SEALANTS AND MOUNTING



Mono component SBR water based adhesive, for bonding structural building elements and thermo-acoustic absorbent materials etc.

Suitable for:

- Structural construction adhesive
- Wood, PVC and ceramic baseboard applications
- Tiles, Ceramics and Polyurethane applications
- Polystyrene and polyurethane panels, frames and rosettes
- Cork and thermo-acoustic materials
- DIY applications
- Laminate and glass materials

TECHNICAL FEATURES:

- + Rapid drying
- + Strong initial tack
- + Thixotropic behaviour
- + Solvent free
- + No shrinkage
- + No nails support required
- + Strong suction cup effect

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust, paints or oils. Any cracks or holes in the wall must be covered with our extra-light filler GLASTER.

ADHESIVE PREPARATION

Mono-component adhesive and ready-to-use. Cut the seal of the cartridge and use a special caulking gun for cartridges

APPLICATION

Apply the product all over the contact surface.

CONSUMPTION

- 200 – 300 g/m² when applied by trowel
- about 20 m (linear) per cartridge

CLEANING

Clean the equipment with fresh water immediately after use, or remove mechanically.

CONTRAINDICATIONS

- Do not use at temperatures below +3 °C
- Application is recommended between +10 °C and +35 °C

www.acm-italy.com

TECHNICAL DATA SHEET

REVISED: 01/09/2022

ADHESIVA SBR

SEALANTS AND MOUNTING



PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30002	300	ml	cartridge	24
30003	6	kg	bucket	1

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 12 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

PRODUCT TECHNICAL DATA

Base	Water -SBR
Appearance and colour	Brown light-dark
Solids percentage	about 80%
Customs code	3506 9100
Application temperature	+10°C +35°C
Waiting Time	None
Open Time	About 30-40 min
Setting Time	48/72 hours

FINAL REGULATIONS

Keep out of reach of children. Discharge the waste in special containers for building materials

DISCLAIMER

The above mentioned information and prescriptions, even if they correspond to our best experience are purely indicative and must be confirmed by practical applications. Therefore before using, it is necessary to establish if it fits the prescribed use and the final customer assumes any responsibility that may derive from its use.