



# ADHESIVA SBR

SINGLE-COMPONENT  
STRUCTURAL ADHESIVE – SBR  
WATER-BASED



TECHNICAL DATA SHEET UPDATED 12/02/2026

## Product Information

Single-component water-based adhesive formulated with SBR resins (styrene-butadiene rubber), specifically designed for bonding structural building elements and acoustic/thermal insulation materials. Provides excellent adhesion even on low-absorption substrates, ensuring a strong and elastic bond.

- + Fast drying
- + High initial tack
- + Thixotropic consistency (non-drip)
- + Solvent-free
- + Minimal shrinkage during drying
- + No need for mechanical fixings (nails or screws)
- + Enhanced suction effect

## Recommended Uses

- Structural elements in construction
- Skirting boards in wood, PVC, or ceramic
- Ceramic tiles and wall coverings
- Decorative panels, moldings, and ceiling roses in polystyrene or polyurethane
- Cork coverings and acoustic/thermal insulation panels
- Thermal insulation boards

## Coverage

200–300 g/m<sup>2</sup>

Estimated yield per cartridge: up to 20 linear meters

## Application Instructions

### Substrate Preparation

All surfaces must be dry, absorbent, sound, and free from dust, paint, or oil residues.

Cracks should be filled with our ultra-light filler GLASTER

### Product Preparation

Ready-to-use product.

For cartridges: cut the seal and apply using a professional caulking gun.

### Product Application

Apply the adhesive to ensure full contact between the surfaces.

Press firmly to ensure uniform wetting of the entire bonding area.

### Cleaning

Clean tools with water while the product is still fresh.

Once cured, residues must be removed mechanically.



# ADHESIVA SBR

SINGLE-COMPONENT  
STRUCTURAL ADHESIVE – SBR  
WATER-BASED



TECHNICAL DATA SHEET UPDATED 12/02/2026

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	30002	300	ml	Cartridge	24
	30003	6	kg	Bucket	1

<b>Technical Data</b>	Base	Water – SBR resins (styrene-butadiene)
	Appearance	Light to dark brown
	Solids content	Approx. 80%
	Customs code	3506 91 00
	Application temperature range	+10 °C to +35 °C (+50 °F to +95 °F)
	Initial grab time	10–15 minutes
	Open time	Approx. 30–40 minutes
	Full drying time	48 hours

<b>Warnings</b>	<ul style="list-style-type: none"><li>Do not apply at temperatures below +3 °C</li><li>Recommended application between +10 °C and +35 °C</li></ul>
<b>Storage</b>	The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. It is important to store the product in a dry place, away from heat sources and direct sunlight.
<b>Final note</b>	Keep out of reach of children and pets. Dispose of waste in designated construction material containers. The information in this technical sheet is based on our extensive experience but is indicative. Users must assess product suitability for their specific use and are responsible for its application.