



ADHESIVA TNT



POWDER ADHESIVE FOR NON-
WOVEN OR VINYL WALL
COVERINGS WITH NON-WOVEN
BACKING

TECHNICAL DATA SHEET UPDATED 12/02/2026

Product Information

Powder adhesive for non-woven or vinyl wall coverings with non-woven backing.

Also compatible with all ACM paste products.

- + Does not stain
- + Strong initial tack
- + High yield
- + Ready to use in just 5 minutes
- + Zero VOC (volatile organic compounds)



- Non-woven wall coverings
- Vinyl wall coverings with non-woven backing
- Glass fiber wall coverings
- Expanded wall coverings with non-woven backing
- Thermal-acoustic insulating wall coverings

Application Instructions

Substrate Preparation

All surfaces must be dry, absorbent, sound, and free from dust, paint, or oil. Any cracks or holes should be filled with our lightweight filler GLASTER, and if needed, skimmed with a standard gypsum-based filler. We recommend using our PRIMER AC for consolidation and cleaning, and PRIMER SP (special anti-mold and antibacterial) for damp walls.

Product Dilution

Dilute the product in clean water according to the ratio shown on the package.

Product Preparation

1. Stir water vigorously.
2. Pour the powder into the water while continuing to stir.
3. Let rest for 3 minutes.
4. Stir again.
5. Ready to use after 5 minutes.

Product Application

Apply the adhesive directly to the back of the wallpaper or to the wall, following the wallpaper manufacturer's instructions.



ADHESIVA TNT



POWDER ADHESIVE FOR NON-WOVEN OR VINYL WALL COVERINGS WITH NON-WOVEN BACKING

TECHNICAL DATA SHEET UPDATED 12/02/2026

Cleaning

Clean any excess adhesive from joints with a damp sponge. THE PRODUCT DOES NOT STAIN.

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	10016-165	165	g	Carton	24
	10016-250	250	g	Carton	24
	10016-500	500	g	Carton	12
	10016-1-12	1	kg	Carton	12

Technical Data

Physical appearance	Powder
Color	White
Solids content	100%
Customs code	3505 2030
Flammability	No
Application temperature	+5 °C to +40 °C
Waiting time	10–20 minutes
Open time	20–30 minutes
Full drying time	48 hours
Non-toxic	Yes
Frost-resistant	Yes

Warnings

- Do not use the adhesive on non-absorbent substrates.
- Do not apply on damp or moldy walls or poorly prepared surfaces.
- Remove any adhesive excess immediately with a damp sponge.



ADHESIVA TNT

POWDER ADHESIVE FOR NON-
WOVEN OR VINYL WALL
COVERINGS WITH NON-WOVEN
BACKING



TECHNICAL DATA SHEET UPDATED 12/02/2026

Storage

The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 60 months from the production date.
It is essential to store the product in a dry place, away from heat sources and direct sunlight.

Final note

Keep out of the reach of children and pets.
Dispose of waste in designated containers for construction materials.

Disclaimer

The information in this technical sheet is based on our long-standing experience but is provided as a guideline.

The user is responsible for determining whether the product is suitable for their specific application and for its use.
