

TECHNICAL DATA SHEET

REVISED: 30/11/2022

ADHESIVA VOV

READY MIXED ADHESIVES FOR WALL COVERINGS



Special PSA paste adhesive, ready-to-use. High adhesion power. Ideal product for application of decorative borders on vinyl or non-absorbent coverings. Excellent for the closure of joints for heavy vinyl wallcoverings.

Suitable for:

- Vinyl and paper edges
- Decorative borders
- Difficult corners and inserts

TECHNICAL FEATURES

- + Exceptional adhesive strength
- + Does not stain
- + High yield

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks or holes in the wall must be covered with our extra-light stucco GLASTER and in case of imperfections shaved with a normal stucco plaster.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet walls with fungi and mold) in case of rising damp or too humid surface.

PRODUCT PREPARATION

Product is a ready-to-use

APPLICATION

Apply the adhesive in a single coat with a brush or roller.

When product is applied directly on the wall or on the joints, directly press and place the wallpaper, before the glue forms a film on the surface.

CONSUMPTION

About 100 -300 gr/m2, when applied with roller or brush

CLEANING

We recommend cleaning the wall coverings from excess adhesive and the joints with a wet sponge. Possible spillages of the adhesive should be removed immediately. We also recommend consulting the cleaning instructions of the wall covering's manufacturer before application. **THE PRODUCT DOES NOT STAIN**

CONTRAINDICATIONS

Do not use on humid walls or with mold. Possible spillages of the adhesive should be removed immediately with a damp sponge.

TECHNICAL DATA SHEET

REVISED: 30/11/2022

ADHESIVA VOV

READY MIXED ADHESIVES FOR WALL COVERINGS



PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30213	700	g	Small Bucket	24
30210	75	ml	Paste Tube	12
30211	150	ml	Paste Tube	12

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 18 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

PRODUCT TECHNICAL DATA

Appearance and colour	Creamy paste
PH	7
Viscosity	8.500 cps
VOC	< 0.005 mg/ m3
Solids percentage	about 45%
Customs code	3505 2010
Application temperature	+5°C +40°C
Waiting Time	0-10 min
Open Time	about 30 min
Drying Time	48 hours
Non Flammable product	
Keep free from frost	

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.