



ADHESIVA VOV

READY-TO-USE SPECIAL
ADHESIVE FOR EDGES AND
JOINTS ON VINYL WALL
COVERINGS



TECHNICAL DATA SHEET UPDATED 12/02/2026

Product Information

Special ready-to-use paste adhesive with very high bonding strength, ideal for applying decorative borders to vinyl wall coverings and other non-absorbent surfaces. It is especially recommended for sealing joints and edges on heavy vinyl wall coverings

- + Exceptional adhesive strength
- + Non-staining
- + High coverage

- Decorative vinyl or paper borders
- Perimeter finishes and profiles
- Joints and edges with difficult adhesion

Coverage

Approx. 100–300 g/m², depending on substrate absorbency and application method (brush or roller).

Application Instructions

Substrate Preparation

All substrates must be dry, absorbent, sound, and free from dust, paint or oil. Any cracks or holes must be filled with our lightweight filler GLASTER, and any surface irregularities must be skimmed with standard gypsum filler. PRIMER AC is recommended for consolidation and cleaning, and PRIMER SP, specifically formulated against mould and bacteria, is recommended for damp walls.

Product preparation

The product is ready to use.

Product application

Apply a single coat of adhesive using a brush or roller. If the adhesive is applied to both the wall and the borders, install the borders immediately, before a surface film forms.

Cleaning

Consult the wall covering manufacturer's cleaning instructions before use. The product does not stain.



ADHESIVA VOV

READY-TO-USE SPECIAL
ADHESIVE FOR EDGES AND
JOINTS ON VINYL WALL
COVERINGS



TECHNICAL DATA SHEET UPDATED 12/02/2026

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	30213	700	g	Jar	24
	30210	75	kg	Tube	12
	30211	150	kg	Tubet	12

Technical Data	Physical state	Creamy paste
	pH	7
	Viscosity	8,500 cps
	VOC content	< 0.005 mg/m ³
	Solids content	Approx. 45%
	Customs code	3505 2010
	Application temperature	+5 °C to +40 °C
	Waiting time	0–15 minutes
	Open time	Approx. 30 minutes
	Complete drying time	48 hours
	Flammability	Non-flammable

Warnings	Do not use on damp walls or on surfaces affected by mould. Remove any adhesive residues immediately with a damp sponge.
Storage	The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. It is essential to store the product in a dry place, away from heat sources and direct sunlight.
Final note	Keep out of the reach of children and pets. Dispose of waste in designated containers for construction materials.



ADHESIVA VOV

READY-TO-USE SPECIAL
ADHESIVE FOR EDGES AND
JOINTS ON VINYL WALL
COVERINGS



TECHNICAL DATA SHEET UPDATED 12/02/2026

Disclaimer

The information in this technical sheet is based on our long-standing experience but is provided as a guideline.

The user is responsible for determining whether the product is suitable for their specific application and for its use.
