

TECHNICAL DATA SHEET

REVISED: 17/04/2023

GLASTER

SEALANTS AND MOUNTING

SMOOTHING FILLERS AND WATERPROOFING COATINGS



Super Lightweight filler with important thermal insulating properties. Particularly suitable for humid environments.

Suitable for:

- Filling holes, cracks, fissures, missing parts on: walls, wood and ceramics. Thickness from 1 mm up to and over 5 cm.
- Wall restoration from rising humidity and heat insulation effects
- Paintable with any kind of paint or water-based varnish
- Great to plaster polystyrene and polyurethane frames and rosettes
- Filling of plasterboard joints
- Indoors use

TECHNICAL FEATURES:

- + Solvent free
- + No cracks
- + No shrinkage
- + No need for sanding
- + Ready-to-use
- + Extra White
- + High yield

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust, paints or oils.

ADHESIVE PREPARATION

Mono-component acrylic-based filler, ready-to-use.

APPLICATION

Apply the product with a semi flexible spatula/blade for fillers

CONSUMPTION

Determined by thickness of filling

CLEANING

Clean the equipment with fresh water immediately after use, or remove mechanically.

CONTRAINDICATIONS

- Do not use at temperatures below +3 °C
- Application is recommended between +10 °C and +35 °C

ACM Italy S.r.l.

Viale Enrico Mattei, 8 - 20010 Casorezzo (Milano) - Telefono +39 02 90361148 r.a. - Fax +39 02 9013173 - e-mail: info@acm-italy.com

C.C.I.A.A. MI-1952713 - Cod. Fisc. e P. IVA 07352030964

TECHNICAL DATA SHEET

REVISED: 17/04/2023

GLASTER

SEALANTS AND MOUNTING

SMOOTHING FILLERS AND WATERPROOFING COATINGS



PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30118-12	250	ml	Small bucket	12
30030	300	ml	Cartridge	24
30119-12	500	ml	Small bucket	12
30120-12-1	1	litre	Small bucket	12
30120-N	4	litres	Bucket	1
30121-N	8	litres	Bucket	1
30122-N	14	litres	Bucket	1

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 24 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

PRODUCT TECHNICAL DATA

Base	Acrylic
Appearance and colour	Dense paste, extra white
Solids percentage	about 80%
Customs code	3506 9100
Application temperature	+10°C +35°C
Waiting Time	None
Open Time	About 30-40 min
Setting Time	48/72 hours

FINAL REGULATIONS

Keep out of reach of children. Discharge the waste in special containers for building materials

DISCLAIMER

The above-mentioned information and prescriptions, even if they correspond to our best experience are purely indicative and must be confirmed by practical applications. Therefore, before using it, is necessary to establish if it fits the prescribed use and the final customer assumes any responsibility that may derive from its use.

ACM Italy S.r.l.

Viale Enrico Mattei, 8 - 20010 Casorezzo (Milano) - Telefono +39 02 90361148 r.a. - Fax +39 02 9013173 - e-mail: info@acm-italy.com

C.C.I.A.A. MI-1952713 - Cod. Fisc. e P. IVA 07352030964