



GLASTER

SUPER LIGHTWEIGHT FILLER



TECHNICAL DATA SHEET UPDATED 12/02/2026

Product Information

Super lightweight acrylic-based filler with excellent thermal insulating properties. Specifically formulated for interior applications, it is particularly suitable for humid environments due to its high breathability and moisture-repair capabilities. It does not shrink or crack, requires no sanding, and is ready-to-use. High-yield and easily paintable with any water-based paint or varnish.

- + Solvent-free
- + No cracking
- + No shrinkage
- + No sanding required
- + Ready-to-use
- + Extra white
- + High yield

Recommended uses

- Filling holes, cracks, fissures, and missing parts on walls, wood, or ceramic (from 1 mm up to over 5 cm)
- Local repair of areas affected by rising damp (with thermal insulating effect)
- Smoothing of polystyrene or polyurethane moldings and rosettes
- Filling of plasterboard joints
- Finishing and repair work in indoor environments

Coverage

The amount of filler required is determined by the thickness of the area being filled

Application Instructions

Substrate Preparation

Surfaces must be dry, absorbent, stable, clean and free of dust, paint, oil, or other release agents.

Product Preparation

Ready-to-use. No mixing or dilution required.

Product Application

Apply with a semi-flexible filling spatula. Shape the product to the desired thickness and smooth the surface. Do not apply at temperatures below +3°C.

Cleaning

Clean tools with water immediately after use. Once hardened, the product can only be removed mechanically.



GLASTER

SUPER LIGHTWEIGHT FILLER



TECHNICAL DATA SHEET UPDATED 12/02/2026

Contraindications

Avoid application below +3°C. Recommended temperature range: +10°C to +35°C.

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	30118-12	250	ml	Jar	12
	30030	300	ml	Cartridge	24
	30119-12	500	ml	Jar	12
	30120-12-1	1	litro	Jar	12
	30120-N	4	litri	Bucket	1
	30121-N	8	litri	Bucket	1
	30122-N	14	litri	Bucket	1

Technical Data	Base	Acrylic
	Physical appearance	Dense extra white paste
	Solids content	Approx. 85%
	Customs code	3506 9100
	Application temperature	+10°C to +35°C
	Waiting time	None
	Open time	About 30–40 minutes
	Initial setting time	0–15 minutes

Warnings	Keep out of reach of children and pets. Dispose of waste in containers for construction materials.
----------	--

Storage	The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date.
---------	--



GLASTER

SUPER LIGHTWEIGHT FILLER



TECHNICAL DATA SHEET UPDATED 12/02/2026

It is essential to store the product in a dry place, away from heat sources and direct sunlight.

Final note

Keep out of the reach of children and pets.

Dispose of waste in designated containers for construction materials.

Disclaimer

The information in this technical sheet is based on our long-standing experience but is provided as a guideline.

The user is responsible for determining whether the product is suitable for their specific application and for its use.
