

# **TECHNICAL DATA SHEET**

REVISED: 01/12/2022

# **PAPEREMOVER**

## **REMOVER PRODUCTS**



A solution for the removal of wallcoverings with non-woven or paper backing, and for digital murals

Suitable for:

- Stripping of wallpapers
- Stripping of vinyl wallcoverings on paper or non-woven substrate
- Stripping of foam wallcoverings
- Duplex
- Stripping of old murals, even washable ones

## **TECHNICAL CHARACTERISTICS**

- + Supremely strong adhesive
- + High yield
- + Low VOC (Volatile Organic Compounds)
- + Contains mould-resistant agent

## **PRODUCT PREPARATION**

We recommend diluting 200g of PAPEREMOVER in up to a maximum 8 litres of water before application. With posters and murals a dilution in 5 litres would be advisable. Once diluted, it can be applied immediately to the area to be removed using roller or a brush. Wait about 10 minutes before removing the wallcovering. Use a metal scraper. On articulates absorbent walls or where the adhesive is especially strong, we suggest using a second application of PAPEREMOVER.

## **APPLICATION**

Once diluted, the product can be applied by roll directly to the area to be stripped.

## **COVERAGE**

Around 40m<sup>2</sup>

## **CLEANING**

The product does not leave marks

## **GUIDANCE**

Where paper-backed vinyl has been used we recommend removing the top layer initially by hand, or by scoring the vinyl surface prior to applying the product.

## **PACKAGING**

<b>PRODUCT CODE</b>	<b>WEIGHT</b>	<b>UNIT</b>	<b>TYPE OF PACKAGING</b>	<b>PCS IN BOX</b>
10012-200	200	g	Plastic bottle	25

[www.acm-italy.com](http://www.acm-italy.com)

# **TECHNICAL DATA SHEET**

REVISED: 01/12/2022

# **PAPEREMOVER**

## **REMOVER PRODUCTS**



### **STORAGE**

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 12 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

### **PRODUCT TECHNICAL DATA**

<b>Base</b>	Surfactant
<b>Physical appearance</b>	liquid
<b>PH</b>	4.5
<b>Viscosity</b>	200cps
<b>Custom code</b>	3505 2010
<b>VOC</b>	<0.005mg/m3
<b>Percentage of solids</b>	Approx 10-15%
<b>Operating Temperature</b>	+5°C +40°C
<b>Waiting time</b>	10-15 minutes
<b>Non inflammable</b>	

### **SAFETY ADVICE**

Keep away from babies and infants. Dispose of waste materials in containers suitable for building products

### **ADVISORY**

The information contained in this technical data sheet, based on results of our long experience, are for information only. Therefore, those who intend to use it are required to assess whether the product is suitable for their use, and to assume responsibility for its use.