



PAPERREMOVER



CONCENTRATED WALLCOVERING REMOVER

TECHNICAL DATA SHEET – UPDATED 12/02/2026

Product Information

The high-efficiency concentrated remover for wallcoverings is formulated to effectively remove a wide range of coverings, including paper, nonwoven fabric, vinyl, and washable wall paints. Its surfactant-based formula ensures deep penetration into the adhesive layers, facilitating removal without damaging the underlying substrate. This product is particularly suitable for removing old glues or from highly absorbent surfaces. In addition, it contains anti-mold additives and has an extremely low VOC content, making it a safer choice for indoor use.

Key benefits include:

- + High removal effectiveness
- + High yield
- + Low VOC content
- + Contains anti-mold agents

Recommended uses

- Removal of traditional wallpaper
- Removal of vinyl wallpaper with paper or nonwoven backing
- Removal of expanded wallcoverings
- Removal of duplex-type wallpapers
- Removal of wall paints, including washable ones

Coverage

Approximately 40 m² per package, depending on the type of wallcovering and substrate absorption.

Application Instructions

Product preparation

Dilute one 200 g bottle in:

- Up to 8 liters of water for wallpaper
- Approximately 5 liters of water for wall paint

Product application

Apply the diluted product evenly to the surface to be treated using a roller or brush.

Cleaning

The product does not stain. Any residues can be removed with water.

Contraindications

For vinyl wallcoverings with paper backing, remove the PVC surface layer first or score the surface to allow the product to penetrate.



PAPERREMOVER

CONCENTRATED WALLCOVERING REMOVER



TECHNICAL DATA SHEET – UPDATED 12/02/2026

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	10012-200	200	g	Bottle	25

Technical Data	Base	Surfactant
	Physical appearance	Liquid
	pH	4.5
	Viscosity	200 cps
	Customs code	3505 2010
	VOC	< 0.005 mg/m ³
	Solids content	Approx. 10–15%
	Application temperature	From +5°C to +40°C
	Waiting time	10–15 minutes
	Flammability	Non-flammable

Warnings	Keep out of reach of children and pets. Dispose of waste in appropriate containers for building materials.
-----------------	--

Storage	The product is guaranteed to be in its original packaging, under standard storage conditions (5°C to 35°C / 41°F to 95°F), for 24 months from the production date. It is essential to store the product in a dry place, away from heat sources and direct sunlight.
----------------	---

Final note	The information provided in this Technical Data Sheet is based on our extensive experience, but is intended as a general guideline. Users must verify the product's suitability for their specific application and take responsibility for its use.
-------------------	---