

PAPEREMOVER

CONCENTRATED
WALLCOVERING REMOVER

TECHNICAL DATA SHEET – UPDATED 17/11/2026

Product Information

High-performance concentrated remover for paper, nonwoven, and vinyl wallcoverings, as well as wall paints, including washable coatings. Its surfactant-based formula penetrates adhesive layers, facilitating removal without damaging the substrate. It is also ideal for surfaces with old adhesive residue or absorbent substrates. Contains mold-inhibiting additives and has a very low VOC content.

+ Superior stripping performance
+ High coverage
+ Very low VOC content
+ Contains mold-inhibiting additives

Recommended uses

- Removal of traditional wallpaper
- Removal of vinyl wallcoverings with paper or nonwoven backing
- Removal of expanded wallcoverings
- Removal of duplex wallpaper
- Removal of old paint layers

Coverage

Approximately 40 m² per container, depending on the type of wallcovering and the absorbency of the substrate.

Application Instructions

Product preparation

Dilute the product with water at a 1:10 ratio.

Product application

Apply the diluted product evenly to the surface using a roller or brush. Allow it to work for 10–15 minutes, then remove the wallcovering.

Cleaning

The product does not leave stains. Any residue can be removed with water.

Application Notes

For vinyl wallcoverings with a paper backing, first remove the PVC top layer or score the surface to facilitate product penetration.

Packaging

PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
10012-200	200	g	Bottle	25

ACM Italy S.r.l. Viale Enrico Mattei, 8 - 20010 Casorezzo (Milan) - Italy
+39 02 90361148 | info@acm-italy.com
www.acm-italy.com



PAPEREMOVER

CONCENTRATED
WALLCOVERING REMOVER

TECHNICAL DATA SHEET – UPDATED 17/11/2026

Technical Data	Base	Surfactants
	Physical appearance	Gel
	pH	6-7
	Viscosity	4,000–5,000 cP
	Customs code	3505 2010
	VOC	< 0.005 mg/m³
	Solids content	Approximately 10–15%
	Application temperature	From +5°C to +40°C
	Waiting time	10–15 minutes
	Flammability	Non-flammable

Safety and Disposal	Keep out of reach of children and pets. Dispose of waste in designated containers for construction materials.
Storage	The product is guaranteed for 24 months from the date of manufacture when stored in its original packaging under standard conditions, from +5 °C to +35 °C (+41 °F to +95 °F). Store in a dry place, away from heat sources and direct sunlight.
Disclaimer	The information provided in this Technical Data Sheet is based on our ten years of experience but is intended for guidance only. The user is responsible for determining the product's suitability for the intended application and assumes responsibility for its use.

ACM Italy S.r.l. Viale Enrico Mattei, 8 - 20010 Casorezzo (Milan) - Italy
+39 02 90361148 | info@acm-italy.com
www.acm-italy.com