

# TECHNICAL DATA SHEET

REVISED: 13/12/2022

## PRIMER AC

### PRIMERS AND WALL PREPARATION



Universal acrylic fixing Primer suitable for wall and floor surfaces. Once the product is diluted, it is applied directly on the surface with a roller or a brush

Suitable for:

- Surfaces preparation of walls and floors.
- Remove dust and consolidating the surfaces, walls or cement-based floor screeds.
- Preparation of the walls for correct application of any kind of wall coverings and wall painting.

### TECHNICAL FEATURES

- + Top effectiveness
- + High yield
- + Low V.O.C. content

### PRODUCT PREPARATION

PRIMER AC has to be diluted with clean water, with a recommended dilution ratio 1:4/5 (1 L of PRIMER AC in 4/5 L of clean water). Before applying a wall paint we recommend a dilution in 5 L of water (1:5)

### PRODUCT APPLICATION

After dilution the PRIMER AC can be immediately applied on the surface with a roller or a brush.

The product dries in 3/4 hours. The drying time can vary based upon the temperature and characteristics of the work environment.

### CONSUMPTION

About 100-200 gr/m<sup>2</sup>, depending on the porosity of the substrate

### CLEANING

We recommend to clean all the work tools with water, immediately after use.

### CONTRA-INDICATIONS

Product is not suitable on non-absorbent surfaces (ceramic, glass, laminates). Protect from frost.

### PACKAGING

| PRODUCT CODE | WEIGHT | UNIT   | TYPE OF PACKAGING | PCS IN BOX |
|--------------|--------|--------|-------------------|------------|
| 30090-1000-N | 1      | litre  | Bottle            | 10         |
| 30091-N      | 5      | litres | Tank              | 4          |
| 30092-N      | 10     | litres | Tank              | 1          |

### STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 12 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

[www.acm-italy.com](http://www.acm-italy.com)

# TECHNICAL DATA SHEET

REVISED: 13/12/2022

## PRIMER AC

### PRIMERS AND WALL PREPARATION



#### TECHNICAL PRODUCT DATA

| Base                    | Acrylic, Water Base |
|-------------------------|---------------------|
| Appearance and colour   | Light blue gel      |
| PH                      | 7.7                 |
| Viscosity               | 1000-1200 cps       |
| Solids percentage       | 35%                 |
| Customs code            | 3209 1000           |
| Application temperature | +5°C +40°C          |
| Drying Time             | 3 / 4 hours         |
| Non-Flammable product   |                     |
| Keep free from frost    |                     |

#### FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

#### DISCLAIMER

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.