

TECHNICAL DATA SHEET

REVISED: 13/12/2022

PRIMER⁺ CB GEL

PRIMERS AND WALL PREPARATION



Special acrylic primer in Gel. PRIMER⁺ CB GEL is specifically suited for gypsum boards and new wall surfaces. To be applied by roller or brush.

Suitable for

- Application on Gypsum board
- Application by roller on new wall surfaces
- Protection and prevention of fungi and mold
- Hardens and protects the wall surface
- Preparation to apply wallpaints and wallcoverings

TECHNICAL FEATURES

- + Ready-to-use
- + Does not drip
- + Physical appearance in GEL
- + Very Low V.O.C.

PRODUCT PREPARATION

PRIMER⁺ CB GEL is a ready-to-use product in Gel form. The product can also be diluted with 15/20% clean water.

PRODUCT APPLICATION

Proceed to apply PRIMER⁺ CB GEL on gypsum boards with a short hair wool roller.

The product dries in 3 hours at 20-23°C. The drying time can vary based upon the temperature and characteristics of the work environment. As it is a GEL, the application is easy and clean, without any drips on the floor

CONSUMPTION

About 90-100 gr/m², depending on the porosity of the substrate

CLEANING

We recommend to clean all the work tools with water, immediately after use.

CONTRA-INDICATIONS

Product is not suitable on non-absorbent surfaces (ceramic, glass, laminates). Protect from frost.

PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30207	2,5	Litres	Rectangular Bucket	6
30208	5	Litres	Rectangular Bucket	2
30209	10	Litres	Rectangular Bucket	1

TECHNICAL DATA SHEET

REVISED: 13/12/2022

PRIMER⁺ CB GEL

PRIMERS AND WALL PREPARATION



STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 12 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

TECHNICAL PRODUCT DATA

Base	Acrylic, Water Base
Appearance and colour	White Gel
PH	7.7
Viscosity	1000-1200 cps
Solids percentage	35%
Customs code	3209 1000
Application temperature	+5°C +40°C
Drying Time	3 hours
Non Flammable product	
Keep free from frost	

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.