



PRIMER+ CB GEL

GEL PRIMER FOR SMOOTH AND NON-POROUS SURFACES



TECHNICAL DATA SHEET – UPDATED 17/02/2026

Product Information	<p>Ready-to-use acrylic gel primer, specifically designed for roller application on non-porous or sealed surfaces. Its special gel formulation makes it an excellent anti-slip adhesion promoter on glass, metal, and drywall. It doesn't drip or stain and provides a smooth, even application, even on vertical surfaces.</p> <ul style="list-style-type: none"> + Ready to use + Odorless + Non-drip + Low VOC content + Gel consistency suitable for vertical applications 				
Recommended uses	<ul style="list-style-type: none"> • Non-porous or sealed surfaces • Drywall and smooth substrates • Glass, metal, and non-absorbent coatings • Roller applications requiring adhesion without dripping 				
Coverage	Approximately 80–100 g/m ² depending on surface porosity.				
Application Instructions	<p>Product preparation The product is ready to use and does not require dilution. Shake well before use.</p> <hr/> <p>Product application Apply with a short-pile roller on clean, dry surfaces free of oily residues. Dries in about 3 hours at 20–23 °C (68–73 °F). Drying time may vary depending on temperature and humidity.</p> <hr/> <p>Cleaning Clean tools with water immediately after use.</p>				
Contraindications	Not suitable for direct application on oily surfaces. Do not apply at temperatures below +5 °C (41 °F). Protect from frost.				
Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	30207	2,5	Liter	Bottle	6
	30208	5	Liters	Rectangular bucket	2
	30209	10	liters	Rectangular bucket	1



PRIMER+ CB GEL

GEL PRIMER FOR SMOOTH AND
NON-POROUS SURFACES



TECHNICAL DATA SHEET – UPDATED 17/02/2026

Technical Data	Base	Water-based acrylic
	Physical appearance	White gel
	pH	7.0
	Viscosity	15,000–25,000 cps
	Solid content	35%
	Customs code	3209 1000
	Application temperature	+5 °C to +40 °C (41 °F to 104 °F)
	Drying time	3 hours
	Flammability	Non-flammable
	Frost resistance	Sensitive to frost

Warnings Keep out of reach of children and pets. Dispose of waste in designated containers for construction materials.

Storage The product is guaranteed to be in its original packaging, under standard storage conditions (5°C to 35°C / 41°F to 95°F), for 24 months from the production date. It is essential to store the product in a dry place, away from heat sources and direct sunlight.

Final note The information provided in this Technical Data Sheet is based on our extensive experience, but is intended as a general guideline. Users must verify the product's suitability for their specific application and take responsibility for its use.