



# REXILGUM LVT

PROFESSIONAL ADHESIVE FOR  
LVT AND RESILIENT FLOOR  
COVERINGS



TECHNICAL DATA SHEET UPDATED 18/02/2026

## Product Information

Ready-to-use, water-based, solvent-free multipurpose adhesive. Ideal for professional installation of all types of resilient flooring: PVC (homogeneous and heterogeneous), natural and synthetic rubber, carpet, linoleum, LVT, and indoor sports floors. Provides excellent adhesion, long working time, and strong initial tack.

- + Excellent open time
- + Strong initial tack
- + Low VOC content
- + High yield
- + Excellent wetting on various types of coverings
- + High-resistance, high-quality, ultra-low-emission dispersion

## Recommended Uses

- Homogeneous and heterogeneous vinyl floors
- LVT tiles and planks
- PVC floors over ceramic or marble
- Linoleum with jute backing
- Natural cork or cork with PVC backing
- Natural rubber flooring with smooth or textured backing

## Coverage

Approximately 300–450 g/m<sup>2</sup>, depending on the substrate and type of covering.

## Application Instructions

### Substrate Preparation

All substrates must be dry, absorbent, sound, and free of dust, paint, or oil. Any cracks should be filled using our two-component epoxy adhesive, EPOXY ECO.

For uneven surfaces, we recommend using a powdered cement-based leveling compound such as our SELF LEVEL FLOORING from the Suprimo line or the ready-to-use leveling compound TILECOAT.

To consolidate and clean the substrate, we suggest our primer PRIMER SP. In cases of rising damp or especially moist substrates, use our PRIMER PU.

### Product Preparation

The product is ready to use.

### Product Application

Apply a single coat with a notched trowel No. 2 directly onto the substrate. Spread only as much adhesive as can be covered within the open time. Wait about 15 minutes (perform a finger test), then place the flooring onto the still-wet adhesive. Press firmly to eliminate air bubbles and ensure full adhesive transfer. Avoid excessive stress on joints. Protect the floor from moisture and direct sunlight during curing.

### Cleaning

Remove excess adhesive with a damp sponge. Clean tools with water.



# REXILGUM LVT

PROFESSIONAL ADHESIVE FOR  
LVT AND RESILIENT FLOOR  
COVERINGS



TECHNICAL DATA SHEET UPDATED 18/02/2026

| Packaging | PRODUCT CODE | WEIGHT | UNIT | PACKAGING | PCS/BOX |
|-----------|--------------|--------|------|-----------|---------|
|           | 20168        | 6      | kg   | Buckets   | 1       |
|           | 20169        | 13     | kg   | Buckets   | 1       |
|           | 20170        | 20     | kg   | Buckets   | 1       |

|                |                         |                                   |
|----------------|-------------------------|-----------------------------------|
| Technical Data | Base                    | Acrylic copolymer                 |
|                | Physical appearance     | Beige cream                       |
|                | pH                      | 6.7                               |
|                | Viscosity               | 35,000–40,000 cps                 |
|                | Solid content           | Approx. 70%                       |
|                | Customs code            | 3506 9190                         |
|                | Application temperature | +5 °C to +40 °C (41 °F to 104 °F) |
|                | Waiting time            | 15–20 minutes                     |
|                | Open time               | 30–40 minutes                     |
|                | Drying time             | 24 hours                          |
|                | Flammability            | Non-flammable                     |

## Warnings

- Not suitable for outdoor applications (use ADHESIVA 2P/G instead).
- Do not apply at temperatures below +3 °C (37.4 °F).
- Avoid using on damp surfaces or where rising moisture is present.
- Pre-treat non-absorbent surfaces to enhance adhesion.
- Do not mix dried surface film that may have formed from improper storage.

## Storage

The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. It is important to store the product in a dry place, away from heat sources and direct sunlight.



# REXILGUM LVT

PROFESSIONAL ADHESIVE FOR  
LVT AND RESILIENT FLOOR  
COVERINGS



TECHNICAL DATA SHEET UPDATED 18/02/2026

---

#### Final note

Keep out of reach of children and pets. Dispose of waste in designated construction material containers.

The information in this technical sheet is based on our extensive experience but is indicative. Users must assess product suitability for their specific use and are responsible for its application.

---