

## RIVESTIMENTI MURALI





TECHNICAL DATA SHEET UPDATED 28/07/2025

### **Product Information**

Powder adhesive suitable for all types of wallcoverings. Can also be used with all paste products from the ACM range.

- + Does not stain
- + Strong initial grip
- + High coverage
- + Ready to use in just 5 minutes
- + Zero VOCs (Volatile Organic Compounds)



- All types of wallcoverings
- Vinyl and heavy vinyl wallcoverings with paper or nonwoven backing
- Duplex wallpapers
- Nonwoven wallcoverings

#### **Application Instructions**

### **Substrate Preparation**

All surfaces must be dry, absorbent, sound, and free from dust, paint, or oil. Any cracks or holes should be filled with our lightweight filler GLASTER, and if needed, skimmed with a standard gypsum-based filler. We recommend using our PRIMER AC for consolidation and cleaning, and PRIMER SP (special anti-mold and antibacterial) for damp walls.

#### **Product Dilution**

Dilute the product in clean water according to the ratio shown on the package.

## **Product Preparation**

- 1. Stir water vigorously.
- 2. Pour the powder into the water while continuing to stir.
- 3. Let rest for 3 minutes.
- 4. Stir again.
- Ready to use after 5 minutes.

## **Product Application**

Apply the adhesive directly to the back of the wallpaper or to the wall, following the wallpaper manufacturer's instructions.



# RIVESTIMENTI MURALI





TECHNICAL DATA SHEET UPDATED 28/07/2025

### Cleaning

Clean any excess adhesive from joints with a damp sponge. THE PRODUCT DOES NOT STAIN.

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX	
	10015-100-100	100	g	Aluminium sachet	100	
	10015-200	200	g	Carton box	24	
	10015-50-250	250	g	Aluminium sachet	50	
	10015-500	500	g	Carton box	12	
	10015-12-1	1	kg	Carton box	12	
		•				
Technical Data	Physical appearance	Physical appearance		White flakes		
	Color	Color		White		
	Solids content	Solids content		100%		
	Customs code	Customs code		3505 2030		
	Flammability	Flammability		No		
	Application temperat	Application temperature		+5 °C to +40 °C		
	Waiting time	Waiting time		10–20 minutes		
	Open time	Open time		20–30 minutes		
	Full drying time	Full drying time		48 hours		
	Non-toxic	Non-toxic		Yes		
	Frost-resistant	Frost-resistant		Yes		



# RIVESTIMENTI MURALI





TECHNICAL DATA SHEET UPDATED 28/07/2025

Warnings	<ul> <li>Do not use the adhesive on non-absorbent substrates.</li> <li>Do not apply on damp or moldy walls or poorly prepared surfaces.</li> <li>Remove any adhesive excess immediately with a damp sponge.</li> </ul>		
Storage	The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 60 months from the production date.  It is essential to store the product in a dry place, away from heat sources and direct sunlight.		
Final note	Keep out of the reach of children and pets.  Dispose of waste in designated containers for construction materials.		
Disclaimer	The information in this technical sheet is based on our long-standing experience but is provided as a guideline.		
	The user is responsible for determining whether the product is suitable for their specific application and for its use.		