



SEACRIL

PAINTABLE ACRYLIC SEALANT



TECHNICAL DATA SHEET UPDATED 18/02/2026

Product Information

One-component acrylic-based sealant, ready to use, paintable, available in white and custom colors (on request). Characterized by suction effect, strong initial tack and high elasticity, it is suitable for sealing and filling applications in construction and DIY.

- + Elongation up to 250%
- + Solvent-free
- + Low shrinkage
- + Low VOC content
- + Does not require nails or mechanical support
- + Strong suction effect
- + Elastic
- + Paintable

Recommended Uses

- Sealing cracks in walls, plasterboard and tiles
- Joints between plasterboard and metal supports
- Fixing of panels, moldings and rosettes in polystyrene or polyurethane
- General DIY applications

Coverage

Up to 15 linear meters per cartridge

200–300 g/m² if applied with spatula

Application Instructions

Substrate Preparation

All surfaces must be dry, absorbent, sound, and free from dust, paint, or oil residues.

Cracks should be filled with our ultra-light filler GLASTER

Product Preparation

Ready-to-use product.

For cartridges: cut the seal and apply using a professional caulking gun.

Product Application

Apply the adhesive to ensure full contact between the surfaces.

Press firmly to ensure uniform wetting of the entire bonding area.

Cleaning

Clean tools with water while the product is still fresh.

Once cured, residues must be removed mechanically.



SEACRIL

PAINTABLE ACRYLIC SEALANT



TECHNICAL DATA SHEET UPDATED 18/02/2026

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	30004	300	ml	Cartridge	24
	30005	6	kg	Bucket	1
	30006	13	kg	Bucket	1
	30007	20	kg	Bucket	1

Technical Data	Base	Acrylic
	Physical appearance	White or colored paste (on request)
	Solids content	approx. 85%
	Customs code	3506 9100
	Application temperature	+10 °C to +35 °C
	Waiting time	None
	Open time	approx. 20 minutes
	Final curing time	24–36 hours

Warnings	<ul style="list-style-type: none">Do not apply at temperatures below +3 °CRecommended application between +10 °C and +35 °C
-----------------	----------------------------------------------------------------------------------------------------------------------------------------------------

Storage	The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. It is important to store the product in a dry place, away from heat sources and direct sunlight.
----------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Final note	Keep out of reach of children and pets. Dispose of waste in designated construction material containers. The information in this technical sheet is based on our extensive experience but is indicative. Users must assess product suitability for their specific use and are responsible for its application.
-------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------