

TECHNICAL DATA SHEET

REVISED: 01/09/2022

SEACRIL PRO

SEALANTS AND MOUNTING



Paintable, acrylic based sealant, extra white, professional use.

Suitable for:

- Sealing cracks on walls, plasterboards and tiles
- Sealing joints between plasterboard and metal supports
- Polystyrene and polyurethane panels, frames and rosettes
- Cork and thermo-acoustic materials
- DIY applications

TECHNICAL FEATURES:

- + Strong suction cup effect
- + Strong initial tack
- + Up to 400% stretch
- + Solvent free
- + Low shrinkage
- + No nails support required
- + Elastic
- + Paintable

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust, paints or oils. Any cracks or holes in the wall must be covered with our extra-light filler GLASTER.

ADHESIVE PREPARATION

Mono-component adhesive and ready-for-use. Cut the seal of the cartridge and use a special caulking gun for cartridges

APPLICATION

Apply the product all over the contact surface.

CONSUMPTION

- About 18 m (linear) per cartridge
- 100-300 g/m² when applied by trowel

CLEANING

Clean the equipment with fresh water immediately after use, or remove mechanically.

CONTRAINDICATIONS

- Do not use at temperatures below +3 °C
- Application is recommended between +10 °C and +35 °C

TECHNICAL DATA SHEET

REVISED: 01/09/2022

SEACRIL PRO

SEALANTS AND MOUNTING



PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
30008	300	ml	Cartridge	24
30009	6	kg	Bucket	1
300010	13	kg	Bucket	1
300011	20	kg	Bucket	1

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 12 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

TECHNICAL PRODUCT DATA

Base	Acrylic
Appearance and colour	Extra White
Solids percentage	about 85%
Customs code	3506 9100
Application temperature	+10°C +35°C
Waiting Time	None
Open Time	About 20 min
Setting Time	24/36 hours

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

The above mentioned information and prescriptions, even if they correspond to our best experience are purely indicative and must be confirmed by practical applications. Therefore before using, it is necessary to establish if it fits the prescribed use and the final customer assumes any responsibility that may derive from its use.