



# TEXRECO EXTREME

ADHESIVE FOR ALL TYPES OF  
WALLCOVERINGS.  
SUITABLE FOR BOTH  
ABSORBENT AND NON-  
ABSORBENT SUBSTRATES.



TECHNICAL DATA SHEET UPDATED 18/02/2026

## Product Information

Ready-to-use paste adhesive for all types of wallcoverings.  
Suitable for both absorbent and non-absorbent substrates.

- + Exceptional adhesive strength
- + Does not stain
- + High yield
- + Low VOC (Volatile Organic Compounds)



- Contract vinyl wallcoverings with fabric or nonwoven backing, up to 1 kg/m<sup>2</sup>
- Fiberglass wallcoverings
- Paintable wallcoverings
- Vinyl wallcoverings with cotton backing
- Difficult applications

## Coverage

150 - 250 g/m<sup>2</sup>

## Application Instructions

### Substrate Preparation

All substrates must be dry, absorbent, resistant and free from dust, paint and oils. Any cracks or holes must be repaired with our lightweight filler GLASTER and, in case of imperfections, leveled with standard gypsum filler. We always recommend the use of our PRIMER AC for consolidation and cleaning, and PRIMER SP, specially formulated against mold and bacteria, in case of damp walls.

### Product preparation

The product is ready to use; if necessary, it can be diluted with up to 5–10% clean water.

### Product application

Apply the adhesive directly to the back of the wallpaper or onto the wall surface, following the manufacturer's instructions.

### Cleaning

Remove any excess product from joints with a damp sponge. THE PRODUCT DOES NOT STAIN.

# TEXRECO EXTREME



ADHESIVE FOR ALL TYPES OF  
WALLCOVERINGS.  
SUITABLE FOR BOTH  
ABSORBENT AND NON-  
ABSORBENT SUBSTRATES.



TECHNICAL DATA SHEET UPDATED 18/02/2026

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	10144	2,5	kg	Rectangular Bucket	6
	10145	5	kg	Rectangular Bucket	2
	10146	10	kg	Rectangular Bucket	1

Technical Data	Base	Starch
	Physical appearance	White cream
	pH	6.5
	Viscosity	65,000–75,000 cps
	VOC	<0.005 mg/m <sup>3</sup>
	Solids content	Approx. 40%
	Customs code	3505 2010
	Application temperature	+5 °C to +40 °C
	Waiting time	0–10 minutes
	Open time	15–20 minutes
	Complete drying	48 hours

Warnings	The product is not suitable for defective substrates or damp walls. For damp walls, we recommend preparing the surface with PRIMER SP and taking corrective measures if moisture persists.
Storage	The product is guaranteed in its original packaging, under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. It is essential to store the product in a dry place, away from heat sources and direct sunlight.
Final note	Keep out of the reach of children and pets.



# TEXRECO EXTREME

ADHESIVE FOR ALL TYPES OF  
WALLCOVERINGS.  
SUITABLE FOR BOTH  
ABSORBENT AND NON-  
ABSORBENT SUBSTRATES.



TECHNICAL DATA SHEET UPDATED 18/02/2026

---

Dispose of waste in designated containers for construction materials.

---

## Disclaimer

The information in this technical sheet is based on our long-standing experience but is provided as a guideline.

The user is responsible for determining whether the product is suitable for their specific application and for its use.

---