

TECHNICAL DATA SHEET

REVISED: 30/11/2022

TEXRECO PM PRO

READY MIXED ADHESIVES FOR WALL COVERINGS



Acrylic based ready-to-use adhesive for all types of wallpaper specifically for paste machine application

Suitable for:

- Vinyl contract wall coverings with paper or non-woven support
- Wall paper
- Expanded vinyl wall coverings
- Non-woven wall coverings
- Fiberglass wall coverings

TECHNICAL FEATURES

- + Excellent adhesive strength
- + Fast adhesion
- + High yield
- + Excellent wash ability once applied on wall

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust or paints or oils. Any cracks or holes in the wall must be covered with our extra-light stucco GLASTER and in case of imperfections shaved with a normal stucco plaster.

We always recommend the use of our PRIMER AC fixative for consolidation and cleaning.

We recommend using our PRIMER SP (specific for wet walls with fungi and mold) in case of rising damp or too humid surface.

PRODUCT PREPARATION

Product is developed specifically for use with wall paper machine, dilute product up to 15% with clean water.

APPLICATION

Apply the adhesive with a wall paper paste machine

CONSUMPTION

About 200 -300 gr/m², depending on the porosity of the substrate

CLEANING

Clean possible spills at the joints with a damp sponge. THE PRODUCT DOES NOT STAIN

CONTRAINDICATIONS

Product is not suitable on non-absorbent substrates, humid walls with mold or on surfaces not perfectly prepared. Spillage of the adhesive should be removed immediately with a damp sponge.

TECHNICAL DATA SHEET

REVISED: 30/11/2022

TEXRECO PM PRO

READY MIXED ADHESIVES FOR WALL COVERINGS



PACKAGING

PRODUCT CODE	WEIGHT	UNIT	TYPE OF PACKAGING	PCS IN BOX
100016	700	g	Bucket	24
100017	5	kg	Bucket	2
100018	10	kg	Bucket	1
100019	15	kg	Bucket	1

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 18 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

TECHNICAL PRODUCT DATA

Base	Acrylic
Appearance and colour	White cream
PH	6.5
Viscosity	55000-65000 cps
VOC	< 0.005 mg/ m3
Solids percentage	about 45%
Customs code	3505 2010
Application temperature	+5°C +40°C
Waiting Time	0-10 min
Open Time	20-30 min
Drying Time	48 hours
Non-Flammable product	
Keep free from frost	

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

Information described in this Technical Data Sheet are based upon our decades long experience but are indicative. Therefore, the user must evaluate if the product is suitable for its specific application and assumes responsibility for its use.

www.acm-italy.com