



# TEXRECO PM PRO

PASTE ADHESIVE FOR ALL  
TYPES OF WALL COVERINGS  
SPECIFICALLY FORMULATED  
FOR PASTING MACHINES



TECHNICAL DATA SHEET UPDATED 18/02/2026

## Product Information

Ready-to-use acrylic-based paste adhesive, specifically formulated for the installation of all types of wallpaper using automatic pasting machines. It guarantees high performance in terms of adhesion strength, coverage, and cleanliness.

- + Excellent adhesive strength
- + Fast tack
- + High coverage
- + Excellent washability on the wall

- Vinyl wall coverings with paper or non-woven backing
- Traditional wallpaper
- Non-woven fabric wall coverings
- Fiberglass wall coverings
- Expanded vinyl wall coverings

## Coverage

Approximately 200–300 g/m<sup>2</sup>, depending on the type of wall covering and the substrate.

## Application Instructions

### Substrate Preparation

All substrates must be dry, absorbent, sound, and free from dust, paint, and oils. Any cracks or holes must be repaired with our lightweight filler GLASTER and, in the case of surface imperfections, leveled with a standard gypsum filler. We recommend the use of our PRIMER AC for consolidation and cleaning, and PRIMER SP, specifically formulated against mold and bacteria, in the case of damp walls.

### Product preparation

The product is ready to use. For application with pasting machines, dilute with clean water up to 15%.

### Product application

Use the adhesive with the pasting machine, strictly following the instructions provided by the equipment manufacturer. Apply the product to the back of the wall covering in accordance with the wallpaper manufacturer's instructions.

### Cleaning

Remove any excess adhesive with a damp sponge. The product does not stain. Always follow the washing and cleaning instructions provided by the wallpaper manufacturer.



# TEXRECO PM PRO

PASTE ADHESIVE FOR ALL  
TYPES OF WALL COVERINGS  
SPECIFICALLY FORMULATED  
FOR PASTING MACHINES



TECHNICAL DATA SHEET UPDATED 18/02/2026

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	100016	700	g	Jar	24
	100017	5	kg	Bucket	6
	100018	10	kg	Bucket	2
	100019	15	kg	Bucket	1

Technical Data	Base	Acrylic
	Physical appearance	White cream
	pH	6.5
	Viscosity	55,000–65,000 cps
	VOC	< 0.005 mg/m <sup>3</sup>
	Solids content	Approx. 45%
	Customs code	3505 2010
	Application temperature	+5°C to +40°C
	Waiting time	0–10 minutes
	Open time	20–30 minutes
	Drying time	48 hours

## Warnings

Do not use the product on non-absorbent substrates. Do not apply on damp walls affected by mould, or on substrates that have not been properly prepared. Any adhesive spills must be removed immediately with a damp sponge.



# TEXRECO PM PRO

PASTE ADHESIVE FOR ALL  
TYPES OF WALL COVERINGS  
SPECIFICALLY FORMULATED  
FOR PASTING MACHINES



TECHNICAL DATA SHEET UPDATED 18/02/2026

---

#### Storage

The product is guaranteed, in its original unopened packaging and under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. Store in a dry place, away from heat sources and direct sunlight.

---

#### Final note

Keep out of reach of children and pets. Dispose of waste in suitable containers for construction materials, in accordance with local regulations.

---

#### Disclaimer

The information provided in this Technical Data Sheet is based on our many years of experience and is to be considered indicative only. Users must verify the suitability of the product for the intended application and assume full responsibility for its use.

---