



# TEXRECO TDV EASY WALL

PASTE ADHESIVE FOR  
FIBERGLASS WALL COVERINGS.



TECHNICAL DATA SHEET UPDATED 19/02/2026

---

## Product Information

Ready-to-use paste adhesive based on natural resins, specifically developed for the application of fiberglass wall coverings. Compatible with all ACM powder products. Ideal for use on absorbent substrates in both residential and professional environments.

- + Good adhesive strength
- + Non-staining
- + High coverage
- + Zero VOC (Volatile Organic Compounds)



- 
- Fiberglass wall coverings
  - Vinyl wallpapers with paper or non-woven backing

---

## Coverage

Approximately 150–250 g/m<sup>2</sup>, depending on the porosity of the substrate.

---

## Application Instructions

### Substrate Preparation

All substrates must be dry, absorbent, sound, and free from dust, paint, and oils. Any cracks or holes must be repaired with our lightweight filler GLASTER and, in the case of surface imperfections, leveled with a standard gypsum filler. We recommend the use of our PRIMER AC for consolidation and cleaning, and PRIMER SP, specifically formulated against mold and bacteria, in the case of damp walls.

---

### Product preparation

The product is ready to use. If necessary, dilute with clean water up to a maximum of 5–10%.

---

### Product application

Apply the adhesive directly to the back of the wallpaper or onto the wall, according to the wallpaper manufacturer's instructions.

---

### Cleaning

Any adhesive residues at the joints must be removed with a damp sponge.  
THE PRODUCT DOES NOT STAIN.

---



# TEXRECO TDV EASY WALL

PASTE ADHESIVE FOR  
FIBERGLASS WALL COVERINGS.



TECHNICAL DATA SHEET UPDATED 19/02/2026

Packaging	PRODUCT CODE	WEIGHT	UNIT	PACKAGING	PCS/BOX
	10007	5	kg	Bucket	2
	10008	10	kg	Bucket	2
	10009	15	kg	Bucket	1

Technical Data		
	Base	Natural resins
	Physical appearance	White cream
	pH	6.5
	Viscosity	35,000–45,000 cps
	VOC	< 0.005 mg/m <sup>3</sup>
	Solids content	Approx. 25%
	Customs code	3505 2010
	Application temperature	+5°C to +40°C
	Waiting time	0–10 minutes
	Open time	20–30 minutes
	Drying time	48 hours

## Warnings

Do not use the product on non-absorbent substrates. Do not apply on damp walls affected by mould or on substrates that are not perfectly prepared. Any adhesive spills must be removed immediately with a damp sponge.

## Storage

The product is guaranteed, in its original unopened packaging and under standard storage conditions (+5 °C to +35 °C / +41 °F to +95 °F), for 24 months from the production date. Store in a dry place, away from heat sources and direct sunlight.



# TEXRECO TDV EASY WALL

---

PASTE ADHESIVE FOR  
FIBERGLASS WALL COVERINGS.



TECHNICAL DATA SHEET UPDATED 19/02/2026

---

**Final note**

Keep out of reach of children and pets. Dispose of waste in suitable containers for construction materials, in accordance with local regulations.

---

**Disclaimer**

The information provided in this Technical Data Sheet is based on our many years of experience and is to be considered indicative only. Users must verify the suitability of the product for the intended application and assume full responsibility for its use.

---