

TECHNICAL DATA SHEET

REVISED: 09/05/2023

UNIFIX ECO

SEALANTS AND MOUNTING



Acrylic based construction adhesive, for building materials and thermo-acoustic absorbent materials

Suitable for:

- Structural construction adhesive
- Wood, PVC and ceramic baseboard applications
- Tiles, Ceramics and Polyurethane applications
- Cork and thermo-acoustic materials
- DIY applications

Technical features:

- + Solvent free
- + Paintable
- + No nails support required
- + Strong suction cup effect
- + Low VOC (Volatile Organic Compounds)

SURFACE PREPARATION

All surfaces must be dry, absorbent, strong, free of dust, paints or oils. Any cracks or holes in the wall must be covered with our extra-light filler GLASTER.

ADHESIVE PREPARATION

Mono-component adhesive and ready-for-use. Cut the seal of the cartridge and use a special caulking gun for cartridges

APPLICATION

Apply the product all over the contact surface.

CONSUMPTION

- About 20 m (linear) per cartridge
- 200-300 g/m² when applied by trowel

CLEANING

Clean the equipment with fresh water immediately after use, or remove mechanically.

CONTRAINDICATIONS

- Do not use at temperatures below +3 °C
- Application is recommended between +10 °C and +35 °C

TECHNICAL DATA SHEET

REVISED: 09/05/2023

UNIFIX ECO

SEALANTS AND MOUNTING



PACKAGING

| PRODUCT CODE | WEIGHT | UNIT | TYPE OF PACKAGING | PCS IN BOX |
|--------------|--------|------|-------------------|------------|
| 30012 | 300 | ml | Cartridge | 24 |
| 30014 | 1 | kg | Small bucket | 24 |
| 30015 | 6 | kg | Bucket | 1 |
| 30016 | 13 | kg | Bucket | 1 |
| 30017 | 20 | kg | Bucket | 1 |

STORAGE

The product is guaranteed in its original packaging, in standard conditions (+5 °C to + 35 °C), for 24 months from date of production. It is important to keep the product in dry conditions, away from heat sources and direct sunlight.

TECHNICAL PRODUCT DATA

| | |
|-------------------------|-----------------|
| Base | Acrylic |
| Appearance and colour | White |
| Solids percentage | about 75% |
| Customs code | 3506 9100 |
| Application temperature | +10°C +35°C |
| Waiting Time | None |
| Open Time | About 30-40 min |
| Setting Time | 48/72 hours |

FINAL REGULATIONS

Keep out of reach of children and pets. Discharge the waste in special containers for building materials

DISCLAIMER

The above mentioned information and prescriptions, even if they correspond to our best experience are purely indicative and must be confirmed by practical applications. Therefore before using, it is necessary to establish if it fits the prescribed use and the final customer assumes any responsibility that may derive from its use.